

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

3500 SYSTEM

146031-01

COPPER ETHERNET I/O MODULE

Used with the applicable Bently Nevada 3500/22M TDI system configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: Bently Nevada 3500/22M Transient Data Interface Module Datasheet 161581 Rev AC

3500/22M Transient Data Interface Module

Datasheet

Cordant™

161581 Rev. AC



Description

The Bently Nevada™ 3500/22M Transient Data Interface (TDI) is the interface between the 3500 monitoring system and compatible software (System 1 Condition Monitoring and Diagnostic software and 3500 System Configuration software). The TDI combines the function of a 3500/20 Rack Interface Module (RIM) with the data collection capability of a communication processor such as TDXnet.

The TDI resides in the slot adjacent to the power supplies of a 3500 rack. It interfaces with M series monitors (3500/40M, 3500/42M, etc.) to continuously collect steady state and transient dynamic (waveform) data and pass this data through an Ethernet link to the host software. Refer to the Compatibility section at the end of this document for more information.

Static data capture capability is standard with the TDI. However, using an optional Channel Enabling Disk will allow the TDI to capture dynamic and high-resolution transient data as well. The TDI incorporates the communication processor function within the 3500 rack.

Although the TDI provides certain functions common to the entire rack, it is not part of the critical monitoring path and has no effect on the proper, normal operation of the overall monitor system for automatic machinery protection. Every 3500 rack requires one TDI or RIM, which always occupies Slot 1 (next to the power supplies).



Baker Hughes 

Specifications

Inputs

Power	
Consumption	10.5 Watts
Data	
Front Panel	USB-B
10Base-T/ 100Base-TX I/O	10Base-T or 100Base-TX Ethernet, autosensing
100Base-FX I/O	100Base-FX Fiber-Optic Ethernet

Outputs

Front Panel LEDs	
OK LED	Indicates when the 3500/22M is operating properly
TX/RX LED	Indicates when the 3500/22M is communicating with the other modules in the rack
TM LED	Indicates when the 3500 rack is in Trip Multiply mode
CONFIG OK LED	Indicates that the 3500 rack has a valid configuration
I/O Module OK Relay	
Function	Indicates when the 3500 rack is operating normally or when a fault has been detected within the rack. User can select either an "OPEN" or "CLOSED" contact to annunciate a NOT OK condition. This relay always operates as "Normally Energized".

Ratings	Standard OK Relay is rated to 5A @ 24 Vdc/120 Vac, 120 Watts/600 VA Switched Power (maximum) OK Relay with gold-plated contacts is rated down to 1 mA @ 1 Vdc (minimum)
Arc Protection	Arc suppressors are provided.

Controls

Front Panel	
Rack reset button	Clears latched alarms and Timed OK Channel Defeat in the rack. Performs same function as "Rack Reset" contact on I/O module
Address switch	Used to set the rack address: 127 possible addresses
Configuration Keylock	Used to place 3500 rack in either "RUN" mode or "PROGRAM" mode. RUN mode allows for normal operation of the rack and locks out configuration changes. PROGRAM mode allows for normal operation of the rack and also allows for local or remote rack configuration. The key can be removed from the rack in either position, allowing the switch to remain in either the RUN or PROGRAM position. Locking the switch in the RUN position allows you to restrict unauthorized rack reconfiguration. Locking the switch in PROGRAM position allows remote reconfiguration of a rack at any time.

Waveform Sampling

- Collection of waveforms for 48 channels.
- DC-coupled waveforms
- Simultaneous Synchronous and Asynchronous data sampled during all operational modes
- User-configurable Synchronous waveform sampling rates:
 - 1024 samples/rev for 2 revolutions
 - 720 samples/rev for 2 revolutions
 - 512 samples/rev for 4 revolutions
 - 360 samples/rev for 4 revolutions
 - 256 samples/rev for 8 revolutions
 - 128 samples/rev for 16 revolutions
 - 64 samples/rev for 32 revolutions
 - 32 samples/rev for 64 revolutions
 - 16 samples/rev for 128 revolutions
- Asynchronous data sampled to support an 800-line spectrum at the following frequency spans:
 - 10 Hz
 - 20 Hz
 - 50 Hz
 - 100 Hz
 - 200 Hz
 - 500 Hz
 - 1000 Hz
 - 2000 Hz
 - 5000 Hz
 - 10 kHz
 - 20 kHz
 - 30 kHz
- Asynchronous data is anti-alias filtered
- Channel Pairs for providing Orbit or synchronous full spectrum presentations can be split among multiple monitors. For asynchronous full spectrums the channels must be within a monitor channel pair (30 kHz frequency span data will not be phase correlated between channel pairs)

Communications

Protocols	
BN Host Protocol	Communication with 3500 Configuration Software, 3500 Data Acquisition Software, and 3500 Display Software
BN TDI Protocol	Communication with System 1 Condition Monitoring and Diagnostic Software
Front Panel	
Communications	USB-B
Protocol Supported	BN Host Protocol
Baud Rate	115.2 kbaud maximum (auto-baud capable)
Cable Length	USB Cable Length: 5 meters (16.4 ft) maximum. A 3 meter (9.8 ft) cable is included with the 3500 rack
Connector	USB-B
10Base-T / 100Base-TX Ethernet I/O	
Communications	Ethernet, 10Base-T and 100Base TX. Conforms to IEEE802.3
Protocol Supported	BN Host Protocol and BN TDI Protocol using Ethernet TCP/IP
Connection	RJ-45 (telephone jack style) for 10Base-T/100Base-TX Ethernet cabling
Cable Length	100 metres (328 feet) maximum
100 Base-FX Ethernet I/O	

Communications	Ethernet, 100Base-FX Fiber Optic, full duplex multimode. Conforms to IEEE802.3u
Protocol Supported	BN Host Protocol and BN TDI Protocol using Ethernet TCP/IP
Connection	MT-RJ Male Fiber Optic connector for 100 Base- FX cabling
Cable Length	2000 metres (6560 feet) maximum, multimode fiber optic cable



The 3500/22M has a MT-RJ Male connector on the unit for Fiber Optic 100 Base-FX cabling therefore you MUST use a MT-RJ Female connector on the fiber optic cable to ensure proper connectivity.

Environmental Limits

TDI Module, 10Base-T/ 100Base-TX I/O, and 100Base-FX I/O

Operating Temperature	-30°C to +65°C (-22°F to +149°F)
Storage Temperature	-40°C to +85°C (-40°F to +185°F)
Humidity	95%, non-condensing

Battery Life

Powered TDI	38 years @ 50°C (122°F)
Unpowered TDI	12 years @ 50°C (122°F)

Physical

TDI Module

Dimensions (Height x Width x Depth)	241.3 mm x 24.4 mm x 241.8 mm (9.50 in x 0.96 in x 9.52 in)
Weight	0.91 kg (2.0 lbs)

I/O Modules

Dimensions (Height x Width x Depth)	241.3 mm x 24.4 mm x 99.1 mm (9.50 in x 0.96 in x 3.90 in)
Weight	0.20 kg (0.44 lbs)

Rack Space Requirements

TDI Module	1 full-height front slot
I/O Modules	1 full-height rear slot

Ordering Considerations

Compatibility

When upgrading your 3500 rack from a 3500/20 RIM to a 3500/22 TDI, there may be 3500 M modules (e.g. 3500/40M) that are not compatible with the 3500/22. Please check with BNTechsupport.com for additional details.

**CAUTION**



Upgrade advisory.
If the RIM I/O is left in the rack when installing a new TDI, it will damage the TDI.

Please perform the upgrade in this order:
1) Remove RIM
2) Remove RIM I/O
3) Insert TDI I/O
4) Insert TDI.

Network Requirements

For complete information on network requirements, refer to the *3500 Hardening Guide* [document 106M9733]. This document can be requested at BNTechsupport.com.

Ordering Information



For the detailed listing of country and product-specific approvals, refer to the [Approvals Quick Reference Guide \(108M1756\)](#).

For additional technical documentation, please log in to bntechsupport.com and access the Bently Nevada Media Library.

3500/22M TDI Module and I/O

3500/22-AA-BB-CC

A: Transient Data Interface Type

01	Standard (use for standard monitoring applications)
-----------	---

B: I/O Module Type

01	10Base-T/100Base-TX Ethernet
02	100Base-FX (Fiber Optic) Ethernet
03	10Base-T/100Base-TX Ethernet with gold-plated OK Relay contacts
04	100Base-FX (fiber optic) Ethernet with gold-plated OK Relay contacts

C: Agency Approval

00	None
01	CSA/NRTL/C (Class 1, Division 2)
02	Multi (CSA, ATEX, IECEx)

3500 22M Dynamic Data Enabling Disk

This disk enables the number of channels of dynamic data (i.e., the ability to collect waveforms) that the TDI will support. There are two levels of dynamic data. Steady-State points are channels that collect waveform data due either to a software command or to an alarm event, and therefore support current values, scheduled waveform capture, and alarm data capture. Transient points provide all the function of a Steady-State point with the additional capability of waveform collection due to parameter variations such as machine speed.

3500/09-AAA-BBB

A: Steady-State Points

000 to 672	Steady-State Points
-------------------	---------------------

B: Transient Points

002 to 672	Transient Points
-------------------	------------------



The sum of the two fields must be equal to or less than 672. One disk can support multiple TDIs.

Ethernet Cables

Standard 10 Base-T/100 Base-TX Shielded Category 5 Cable with RJ-45 connectors (solid conductor)

138131-AAA

A: Cable Length

006	6 feet (1.8 m)
010	10 feet (3.0 m)
025	25 feet (12.2 m)
040	40 feet (12.2 m)
050	50 feet (15.2 m)
075	75 feet (22.9 m)
085	85 feet (25.9 m)
100	100 feet (30.5 m)
120	120 feet (36.6 m)
150	150 feet (45.7 m)
200	200 feet (61.0 m)
250	250 feet (76.2 m)
320	320 feet (97.5 m)



Standard lengths for 10Base-T/100Base-TX cabling are shown above.

Fiber Optic Cable

100 Base-FX fiber optic cable with MT-RJ female connectors.

175M0075-AAAA

A: Cable Length in feet up to 1000 ft (300 m)

0010	10 feet (3.0 m)
0100	100 feet (30.5 m)
0150	150 feet (45.7 m)
0330	330 feet (100.6 m)
0500	500 feet (152.4 m)
1000	1000 feet (304.8 m)

Spares

288055-01	Standard Transient Data Interface Module with USB cable
123M4610*	10 foot A to B USB cable
146031-01	10Base-T/100Base-TX I/O Module
146031-02	100Base-FX (Fiber Optic) I/O Module
161580	3500/22M TDI Operation and Maintenance User Guide
164466	Network Accessories Datasheet
00580441	Connector header, internal termination, 3-position, green
00580436	Connector header, internal termination, 6-position, green
111M5777	Connector header, internal termination, 2-position, green
166M2390	Connector header, push-in-spring type (alternative for PN 00580436)
166M4363	Connector header, push-in-spring type (alternative for PN 00580441)
146031-03	10Base-T/100Base-TX I/O Module GLD Plated