

AMIKON TECHNICAL DOCUMENTATION

Product Data Sheet

Bently Nevada 330854-040-25-05

Proximity Transducer Extension Cable

TYPE	REFERENCE	SCOPE	OPTIONS
Cable	163236	See table	Check order

330854-040-25-05 - Proximity transducer extension cable. Use only the documented component configuration.

01

VERIFIED PRODUCT IDENTITY

Product model	330854-040-25-05
Cable length	4 m
Cable selection	High-temperature FluidLoc cable
Armor	Flexible AISI 302 stainless steel with PFA jacket
Cable construction	75 ohm triaxial
Cable insulation	PFA
Minimum bend radius	25.4 mm
Operating and storage range	-35 to +200 deg C

Datasheet 163236 Rev. M. Verify the complete supplied product identity.

02 TECHNICAL DATA

Connector material	Gold-plated brass or beryllium copper
Maximum connector torque	0.565 N m
Connector tightening	Finger tight

03 APPLICATION AND CONFIGURATION

- Turbine differential-expansion channels
- Opposite-side collar installations
- Compensated ramp measurement systems
- Match documented component and system requirements
- Verify actual product markings before installation

04 OFFICIAL DOCUMENTATION

Datasheet 163236 Rev. M

Selected manufacturer data applies to the identified component and documented conditions. Check the full ordering configuration. Consult the applicable installation instructions before selecting, installing or replacing equipment.

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM