

AMIKON TECHNICAL DOCUMENTATION

Product Data Sheet

Bently Nevada 330130-060-00-05

Proximity Transducer Extension Cable

TYPE	REFERENCE	SCOPE	OPTIONS
Cable	141194	See table	Check order

330130-060-00-05 - Proximity transducer extension cable. Use only the documented component configuration.

01

VERIFIED PRODUCT IDENTITY

Product model	330130-060-00-05
Cable length	6 m
Cable selection	Standard cable
Aarmor	Without armor
Cable construction	75 ohm triaxial
Cable insulation	FEP
Minimum bend radius	25.4 mm
Operating and storage range	-52 to +177 deg C

Datasheet 141194 Rev. AM. Verify the complete supplied product identity.

02 TECHNICAL DATA

Connector material	Gold-plated brass or beryllium copper
Maximum connector torque	0.565 N m
Connector tightening	Finger tight

03 APPLICATION AND CONFIGURATION

- Fluid-film bearing vibration channels
- Position-monitoring probe connections
- Keyphasor sensing-chain connections
- Match documented component and system requirements
- Verify actual product markings before installation

04 OFFICIAL DOCUMENTATION

Datasheet 141194 Rev. AM

Selected manufacturer data applies to the identified component and documented conditions. Check the full ordering configuration. Consult the applicable installation instructions before selecting, installing or replacing equipment.

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM