

SIMATIC HMI OPERATOR SYSTEMS

Product Data Sheet

6AV6645-0CA01-0AX0

mobile HMI operator panel

FUNCTION mobile HMI operator panel	FAMILY SIMATIC HMI operator systems	ORIGIN Austria	WEIGHT 2.793 kg
--	---	--------------------------	---------------------------

Siemens SIMATIC HMI 6AV6645-0CA01-0AX0 is a mobile HMI operator panel for the SIMATIC HMI operator systems. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Screen diagonal	7.5 in
Horizontal image resolution	640 pixel
Vertical image resolution	480 pixel
min.	0 °C
max.	40 °C
Ambient temperature during storage/transportation min.	-20 °C
Ambient temperature during storage/transportation max.	60 °C
Supports protocol for PROFINET IO	Yes
PROFIsafe	No
Interfaces/bus type	1x RS 422, 1x RS 485, 1x Ethernet (RJ45) (max. 12 Mbit/s)

- Display live process and machine status: Use 6AV6645-0CA01-0AX0 for configured screens, status values and navigation within the documented SIMATIC HMI operator systems. Restore the approved HMI project and communication settings.
- Acknowledge alarms and issue controlled commands: Verify key, touch and safety-control functions on 6AV6645-0CA01-0AX0; confirm each command reaches the intended controller tag without unintended equipment movement.
- Validate the complete operator interface: Test display quality, touch or key response, communication, user access and emergency or enabling devices applicable to 6AV6645-0CA01-0AX0 before production use.

Match 6AV6645-0CA01-0AX0 to the installed SIMATIC HMI operator systems, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[Siemens Industry Mall technical product data](#)

<https://mall.industry.siemens.com/mall/en/kettanehjoown/Catalog/Product?SiepCountryCode=OE&mlfb=6AV6645-0CA01-0AX0>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM