

OFFICIAL MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

6ES7417-4HL01-0AB0

Siemens official documentation for the exact article number.

Source: 6ES7417-4HL01-0AB0.pdf

Selected official Siemens pages follow this cover.

SIMATIC S7-400H, CPU 417H CENTRAL UNIT FOR S7-400H 4
INTERFACES: 1 MPI/DP, 1 DP A. 2 FOR SYNC MODULES 4MB
MEMORY (2MB CODE/2MB DATA)

Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
Input current	
from backplane bus 5 V DC, typ.	1.8 A
from backplane bus 5 V DC, max.	2 A
from backplane bus 24 V DC, max.	300 mA; Total current consumption of the components connected to the MPI/DP interfaces, but no more than 150 mA per interface
Power loss	
Power loss, typ.	10 W
Memory	
Work memory	
• integrated	4 Mbyte
• integrated (for program)	2 Mbyte
• integrated (for data)	2 Mbyte
• expandable	Yes
• expandable, max.	20 Mbyte; up to 10 MB for program, up to 10 MB for data
Load memory	
• expandable FEPR0M	Yes; with Memory Card (FEPR0M)
• expandable FEPR0M, max.	64 Mbyte
• integrated RAM, max.	256 kbyte
• expandable RAM	Yes; with Memory Card (RAM)
• expandable RAM, max.	64 Mbyte
Backup	
• present	Yes
• with battery	Yes; all data
• without battery	No
Battery	
Backup battery	
• Backup current, typ.	75 µA
• Backup current, max.	860 µA
• Feeding of external backup voltage to CPU	5 V DC to 15 V DC
CPU processing times	

for bit operations, typ.	0.1 µs
for word operations, typ.	0.1 µs
for fixed point arithmetic, typ.	0.1 µs
for floating point arithmetic, typ.	0.6 µs
CPU-blocks	
DB	
• Number, max.	8 192; DB 0 reserved
• Size, max.	64 kbyte
FB	
• Number, max.	6 144
• Size, max.	64 kbyte
FC	
• Number, max.	6 144
• Size, max.	64 kbyte
OB	
• Number, max.	see instruction list
• Size, max.	64 kbyte
Counters, timers and their retentivity	
S7 counter	
• Number	512
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	Z 0 to Z 7
Counting range	
— lower limit	1
— upper limit	999
IEC counter	
• present	Yes
• Type	SFB
S7 times	
• Number	512
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
Data areas and their retentivity	
Flag	

• Number, max.	16 kbyte
• Retentivity available	Yes; MB 0 to MB 16383
• Retentivity preset	MB 0 to MB 15
Address area	
I/O address area	
• Inputs	16 kbyte
• Outputs	16 kbyte
Process image	
• Inputs, adjustable	16 kbyte; adjustable at the expense of the code area of the RAM
• Outputs, adjustable	16 kbyte; adjustable at the expense of the code area of the RAM
• Inputs, default	1 024 byte
• Outputs, default	1 024 byte
Subprocess images	
• Number of subprocess images, max.	8
Digital channels	
• Inputs	131 072
— of which central	131 072
• Outputs	131 072
— of which central	131 072
Analog channels	
• Inputs	8 192
— of which central	8 192
• Outputs	8 192
— of which central	8 192
Hardware configuration	
Number of expansion units, max.	21
Multicomputing	No
Interface modules	
• Number of connectable IMs (total), max.	6
• Number of connectable IM 460s, max.	6
• Number of connectable IM 463s, max.	6
Number of DP masters	
• integrated	2
• via CP	10
• via IM 467	0
• Mixed mode IM + CP permitted	No; IM 467 cannot be used jointly with CP 443-5 Ext.
• via interface module	0
Number of operable FMs and CPs (recommended)	
• FM	64; Limited by number of slots and number of connections
• CP, PtP	64; Limited by number of slots and number of connections
• CP, LAN	64; Limited by number of slots and number of connections

Slots	
• required slots	2
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
Operating hours counter	
• Number	8
Clock synchronization	
• supported	Yes
1. Interface	
Physics	RS 485 / PROFIBUS
Isolated	Yes
Protocols	
• MPI	Yes; Default setting
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	No
MPI	
• Number of connections	44
• Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
PROFIBUS DP master	
• Number of connections, max.	32; of which 1 reserved for PG, 1 for OP
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	32; Number of slots, max. 512
Services	
— PG/OP communication	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	No
— S7 communication, as client	No
— S7 communication, as server	No
— Equidistance	No
— SYNC/FREEZE	No
— Activation/deactivation of DP slaves	No