

OFFICIAL MANUFACTURER DOCUMENT PACKAGE

Installation Instructions

6GK5204-2BC10-2AA3

Siemens official documentation for the exact article number.

Source: 6GK5204-2BC10-2AA3.pdf

Selected official Siemens pages follow this cover.

Type of electrical connection	
• for signaling contact • for power supply	2-pole terminal block 4-pole terminal block
design of the removable storage	
• C-PLUG	Yes
Signal-Inputs/outputs	
Operating voltage / of the signaling contacts	
• at DC / Rated value	24 V
Operating current / of the signaling contacts	
• at DC / maximum	0.1 A
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage	
• external • external	24 V 18 ... 32 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.6 A / 60 V
Consumed current / maximum	0.265 A
Power loss [W]	
• at DC / at 24 V	6.36 W
Permitted ambient conditions	
Ambient temperature	
• during operation • during storage • during transport	-40 ... +60 °C -40 ... +70 °C -40 ... +70 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP30
Design, dimensions and weight	
Design	compact
Width	60 mm
Height	125 mm
Depth	124 mm
Net weight	0.78 kg
Mounting type	
• 35 mm DIN rail mounting • wall mounting • S7-300 rail mounting • S7-1500 rail mounting	Yes Yes Yes No