

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

SIEMENS SCALANCE

6GK1105-2AB10

OPTICAL INDUSTRIAL ETHERNET SWITCH

Applicable product family: SIMATIC NET optical networks

OFFICIAL SOURCE

6GK1105-2AB10.pdf

The following pages are selected from the supplied manufacturer document and retain their original page content.

Product type designation

OSM TP62
SIMATIC NET, OSM TP62 OPTICAL SWITCH MODULE W. 2 FOC
CABLE PORTS 100MBIT/S, 6 RJ45 PORTS, 10/100MBIT/S AND 8
DIGITAL INPUTS, REDUN. 24V DC SUPPLY, SIGNALLING
CONTACT, INTEGRATED REDUNDANCY MANAGER W.
NETWORK MANAGEMENT



Transmission rate		
Transfer rate	10 Mbit/s, 100 Mbit/s	
Interfaces / for communication / integrated		
Number of electrical connections	6	
• for network components or terminal equipment		
Number of 100 Mbit/s ST(BFOC) ports	2	
• for multimode		
Number of 100 Mbit/s SC ports	0	
• for multimode		
Number of 1000 Mbit/s LC ports	0	
• for multimode		
• for single mode (LD)		
Interfaces / others		
Number of electrical connections	1	
• for signaling contact		
• for power supply		
• for redundant voltage supply	1	

Type of electrical connection	
• for signaling contact • for power supply	On 6-pole terminal block 6-pole plug-in terminal block

Signal-Inputs/outputs

Operating voltage / of the signaling contacts	
• at DC / Rated value	24 V
Operating current / of the signaling contacts	
• at DC / maximum	0.1 A
Number of digital inputs	8
Number of electrical connections / for digital input signals	2
Type of electrical connection / for digital input signals	4-pole plug-in terminal block
Signal voltage	
• for signal <0> / at DC — Rated value • for signal <1> / at DC — Rated value	-30 ... +3 V 24 V 13 ... 30 V 24 V
Input current / at digital input	
• with signal <0> / maximum • for signal <1>	0.008 mA 0.008 A

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	
• external • external	24 V 18 ... 32 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	T 1.6 A / 250 V
Consumed current / maximum	1 A
Power loss [W]	
• at DC / at 24 V	20 W

Permitted ambient conditions

Ambient temperature	
• during operation • during storage • during transport	0 ... 60 °C -40 ... +80 °C -40 ... +80 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Width	217 mm
-------	--------

Height	161 mm
Depth	69 mm
Net weight	1.4 kg
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes
• S7-300 rail mounting	No
• S7-1500 rail mounting	No
• fixed-mounted	Yes

Product properties, functions, components / general

Cascading in the case of a redundant ring / at reconfiguration time of $< \sim 0.3 \text{ s}$	50
Cascading in cases of star topology	any (depending only on signal propagation time)

Product functions / management, configuration

Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• RMON	Yes
• Port mirroring	Yes
• multiport mirroring	No
• switch-managed	Yes
Protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	Yes
• SNMP v1	Yes

Product functions / Diagnosis

Product function	
• Statistics Packet Size	Yes
• Statistics packet type	Yes
• Error statistics	Yes

Product functions / DHCP

Product function	
• DHCP client	Yes

Product functions / Redundancy

Product function	
------------------	--

• Ring redundancy	Yes
• High Speed Redundancy Protocol (HRP)	Yes
• high speed redundancy protocol (HRP) with redundancy manager	Yes
• high speed redundancy protocol (HRP) with standby redundancy	Yes
Product function	
• media redundancy protocol (MRP) with redundancy manager	Yes
• Parallel Redundancy Protocol (PRP)/operation in the PRP-network	No
• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No

Product functions / Time

Product function	
• SICLOCK support	Yes

Standards, specifications, approvals

Standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T.. A, CL.1, Zone 2, GP. IIC, T4
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
• for emitted interference	EN 61000-6-4
• for interference immunity	EN 61000-6-2
Certificate of suitability / CE marking	Yes
Certificate of suitability	
• C-Tick	Yes
• KC approval	No
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Germanische Lloyd (GL)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
• Polski Rejestr Statkow (PRS)	Yes

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com

- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

06/13/2017 