

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

SIEMENS SINUMERIK

6FC5370-4AM20-0AA0

SINUMERIK OPERATOR PANEL CONTROL UNIT

Applicable product family: SINUMERIK CNC systems

OFFICIAL SOURCE

6FC5370-4AM20-0AA0.pdf

The following pages are selected from the supplied manufacturer document and retain their original page content.

SIEMENS

Data sheet for SINUMERIK 828D PPU 240.2



Figure similar

MLFB-Ordering data6FC5370-4AM20-0AA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data		General tech. specifications	
Input voltage	DC 24 V +20 % -15 %	Mains buffering time	3 ms, 20 ms mit SITOP smart power supply
Power consumption, max.	60 W	Ambient conditions	
Mechanical data		Ambient temperature	
Mounting position	Vertical	Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operator panel	Vertical	Operation at the rear	0 ... 55 °C (32 ... 131 °F)
Net weight	4.50 kg (9.92 lb)	Storage	-25 ... 55 °C (-13 ... 131 °F)
Width	310.0 mm (12.20 in)	Transport	-20 ... 60 °C (-4 ... 140 °F)
Height	380.0 mm (14.96 in)	Relative humidity	
Depth	105.0 mm (4.13 in)	Operation	5 ... 90 %
Degree of protection		Storage	10 ... 100 %
Front side	IP65 With the front flap closed	Transport	5 ... 95 %
Rear side	IP20 / UL open type		