

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

SIEMENS SIMATIC NET

6GK7443-1EX20-0XE0

CP 443-1 ETHERNET COMMUNICATION PROCESSOR

Applicable product family: SIMATIC S7-400 communication processors

OFFICIAL SOURCE

6GK7443-1EX20-0XE0.pdf

The following pages are selected from the supplied manufacturer document and retain their original page content.

Product type designation

CP 443-1

Communications processor CP 443-1 for connection of SIMATIC S7-400 to industrial Ethernet over ISO, TCP/IP and UDP, S7 communication, fetch/write, SEND/RECEIVE with and without RFC1006 Multicast, PROFINET IO Controller, DHCP, SNMP V2, Web, diagnostics, initialization via LAN, access protection via IP access list integrated real-time switch ERTEC 400, 2xRJ45 Anschluss for LAN with 10/100 Mbit/s



Transmission rate

Transfer rate

- at the 1st interface

10 ... 100 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

2

Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet

2

Type of electrical connection

- at the 1st interface / acc. to Industrial Ethernet

RJ45 port

design of the removable storage / C-PLUG

No

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Relative symmetrical tolerance / at DC

- at 5 V

5 %

Consumed current

- from backplane bus / at DC / at 5 V / typical

1.4 A

Power loss [W]	7.25 W
Ambient temperature - during operation - during storage - during transport	0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
Relative humidity at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

(unit format)	Compact module S7-400 single width
Width	25 mm
(height)	290 mm
Depth	210 mm
(net weight)	0.7 kg

Product properties, functions, components / general

Number of units - per CPU / maximum - Note	14 max. 4 as PN IO ctrl.
---	-----------------------------

Performance data / open communication

Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	64
Amount of data - as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum - as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum - as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum - as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte 8 Kibyte 8 Kibyte 2 Kibyte
Number of possible connections / for open communication by means of T blocks / maximum	64
Amount of data as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum	1452 byte

Performance data / S7 communication

Number of possible connections / for S7 communication

- maximum 128
- with PG connections / maximum 2
- Note when using several CPUs

Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode

128

Performance data / PROFINET communication / as PN IO-Controller

Product function / PROFINET IO controller

Yes

Number of PN IO devices / on PROFINET IO controller / usable / total

128

Number of PN IO IRT devices / on PROFINET IO controller / usable

128

Number of external PN IO lines / with PROFINET / per rack

4

Amount of data

- as user data for input variables / as PROFINET IO controller / maximum 4 Kibyte
- as user data for input variables / as PROFINET IO controller / maximum 4 Kibyte
- as user data for input variables per PN IO device / as PROFINET IO controller / maximum 1433 byte
- as user data for output variables per PN IO device / as PROFINET IO controller / maximum 1433 byte
- as user data for input variables per PN IO device / for each sub-module as PROFINET IO controller / maximum 240 byte
- as user data for output variables per PN IO device / for each sub-module as PROFINET IO controller / maximum 240 byte

Product functions / management, configuration

Product function / MIB support

Yes

Protocol / is supported

- SNMP v1 Yes
- DCP Yes
- LLDP Yes

Configuration software

- required STEP 7 V5.4 SP4 or higher

Product functions / Diagnosis

Product function / Web-based diagnostics

Yes

Product functions / switch

Product feature / Switch	Yes
Product function	
• switch-managed	No
• with IRT / PROFINET IO switch	Yes
• Configuration with STEP 7	Yes

Product functions / Redundancy

Product function	
• Ring redundancy	Yes
• Redundancy manager	Yes
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes

Product functions / Security

Product function	
• password protection for Web applications	No
• ACL - IP-based	Yes
• ACL - IP-based for PLC/routing	No
• switch-off of non-required services	Yes
• Blocking of communication via physical ports	Yes
• log file for unauthorized access	No

Product functions / Time

Product function / SICLOCK support	Yes
Product function / pass on time synchronization	Yes
Protocol / is supported	
• NTP	Yes

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

04/11/2019 