

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

SIEMENS SCALANCE

6GK5632-2GS00-2AC2

SCALANCE SC632-2C SECURITY APPLIANCE

Applicable product family: SCALANCE S industrial security

OFFICIAL SOURCE

6GK5632-2GS00-2AC2.pdf

The following pages are selected from the supplied manufacturer document and retain their original page content.

product type designation



SC632-2C

SCALANCE SC632-2C Industrial Security Appliance; For protection of devices and networks in discrete manufacturing and the process industry for protection of the industrial communication with firewall; Further functions: address conversion (NAT/NAPT); Connection to SINEMA RC; 2x combo port electrical or optical; 10/100/1000 Mbit/s RJ45 or 100 Mbit/s SFP or 1000 Mbit/s SFP.

transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	2
number of electrical connections	
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
type of electrical connection	
• for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block
design of the removable storage / C-PLUG	Yes
signal inputs/outputs	
number of electrical connections	
• for digital input signals	1
type of electrical connection	
• for digital input signals	2-pole terminal block
operating voltage / of the signaling contacts / at DC / rated value	24 V
operational current / of the signaling contacts / at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
supply voltage / 1 / rated value	24 V; (with plugged-in SFPs)
power loss [W] / 1 / rated value	9.12 W
supply voltage / 1 / rated value	9.6 ... 31.2 V
consumed current / 1 / maximum	0.38 A
ambient conditions	
ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	compact
width	60 mm
height	145 mm

depth	125 mm
net weight	0.58 kg
fastening method	Fixing bolt with additional screw protection
fastening method • 35 mm top hat DIN rail mounting • S7-300 rail mounting • S7-1500 rail mounting • wall mounting	Yes Yes Yes Yes
product features, product functions, product components / general	
product function / DynDNS client	Yes
product functions / management, configuration, engineering	
product function • CLI • web-based management • MIB support	Yes Yes Yes
protocol / is supported • HTTP • SNMP v1 • SNMP v2 • SNMP v3	No Yes Yes Yes
type of configuration	WBM, CLI, SNMP
product functions / diagnostics	
product function • SysLog • packet filter log • audit log • system log	Yes Yes Yes Yes
product functions / DHCP	
product function • DHCP client • DHCP server - internal network	Yes Yes
product functions / routing	
product function / static IP routing	Yes
product functions / security	
firewall version	stateful inspection
product function / with VPN connection	OpenVPN (as client for SINEMA RC)
product function • password protection • bandwidth limitation • NAT/NAPT	Yes No Yes
product functions / time	
protocol / is supported / NTP	Yes
product feature / hardware real time clock w. battery backup	Yes
standards, specifications, approvals	
standard • for FM • for safety / from CSA and UL • for emitted interference • for interference immunity	FM 3611 (available soon) UL 60950 / CSA C22.2 No. 60950-1-03, CSA C22.2 No. 213-M1987 (in preparation) EN 61000-6-4: 2007 EN 61000-6-2: 2005
certificate of suitability • CE marking • C-Tick	AS/NZS 2064 (Class A), EN 61000-6-2, EN 61000-6-4 Yes Yes
standards, specifications, approvals / marine classification	
Marine classification association • American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • DNV GL	Yes Yes Yes

• Korean Register of Shipping (KRS) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS) • Royal Institution of Naval Architects (RINA)	Yes Yes Yes Yes Yes
standards, specifications, approvals / hazardous environments	
standard / for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
accessories	
product extension / optional / C-PLUG	Yes
further information / internet-Links	
Internet-Link • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support	http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

2/21/2022 