

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

SIEMENS SIMATIC S7

7MH4980-2AA01

SIWAREX WP522 ST WEIGHING MODULE

Applicable product family: SIMATIC weighing systems

OFFICIAL SOURCE

7MH4980-2AA01.pdf

The following pages are selected from the supplied manufacturer document and retain their original page content.



SIMATIC S7-1500, TM SIWAREX WP522 ST, two-channel weighing module for two platform or hopper scales with analog load cells / strain gauges (full bridges), 3xDI, 3xDQ, 1xRS485, 1xEthernet, 2xLC load cell interface (1-4mV/V)

General information	
Product type designation	TM SIWAREX WP522 ST
Firmware version	V1.0.0
• FW update possible	Yes
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	Yes
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	STEP 7 V14 or higher
• PROFIBUS from GSD version/GSD revision	GSD Revision 5
• PROFINET from GSD version/GSD revision	GSDML
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	19.2 V
• permissible range, upper limit (DC)	28.8 V
• Reverse polarity protection	Yes
Power	
Power consumption from the backplane bus	0.55 W
Power loss	
Power loss, typ.	3.9 W
Address area	
Address space per module	
• Inputs	64 byte
• Outputs	64 byte
Digital inputs	
Number of digital inputs	6; 3 per channel
Digital inputs, parameterizable	Yes
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Digital outputs	
Number of digital outputs	8; 4 per channel
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes
Digital output functions, parameterizable	
• Switching tripped by comparison values	Yes
• Freely usable digital output	Yes
Switching capacity of the outputs	
• with resistive load, max.	0.5 A; Per digital output

Output voltage	
• Type of output voltage	DC
Output delay with resistive load	
• "0" to "1", max.	65 μ s
• "1" to "0", max.	110 μ s
Total current of the outputs	
• Current per module, max.	8 A
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Encoder	
Connection of signal encoders	
• For strain gauges (full bridges) with 4-conductor connection	Yes
• For strain gauges (full bridges) with 6-conductor connection	Yes
• Resistance of full bridge, min.	40 Ω
• Resistance of full bridge, max.	4 100 Ω
Interfaces	
Number of RS 485 interfaces	1
1. Interface	
Interface types	
• RS 485	Yes
2. Interface	
Interface types	
• RJ 45 (Ethernet)	Yes; 10/100 Mbit/s
• Number of ports	1
Interrupts/diagnostics/status information	
Substitute values connectable	Yes
Alarms	
• Diagnostic alarm	Yes
• Hardware interrupt	Yes
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire-break	Yes
• Short-circuit	Yes
Diagnostics indication LED	
• RUN LED	Yes
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
Integrated Functions	
Counter	No
Fast mode	No
Load cell	
• Non-automatic weighing instrument	NAWI
• Sampling rate	100 Hz
• Resolution of input signal	$\pm 1\,000\,000$ parts pro mV/V
• Common mode voltage, min.	0.25 V
• Common mode voltage, max.	4.75 V
• Cable length, max.	800 m; when using the SIWAREX 7MH4702-8AG cable
Measuring functions	
Measuring range	
— -1 mV/V to +1 mV/V	Yes
— -2 mV/V to +2 mV/V	Yes
— -4 mV/V to +4 mV/V	Yes
Potential separation	
Potential separation channels	
• between the channels and backplane bus	Yes