

SCALANCE X-200 MANAGED SWITCHES

Product Data Sheet

6GK5224-0BA00-2AA3

managed Industrial Ethernet switch

FUNCTION managed Industrial Ethernet switch	FAMILY SCALANCE X-200 managed switches	ORIGIN Germany	WEIGHT 0.88 kg
---	--	--------------------------	--------------------------

Siemens SCALANCE 6GK5224-0BA00-2AA3 is a managed Industrial Ethernet switch for the SCALANCE X-200 managed switches. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Product Designation	SCALANCE X224
RJ45 Ports	24
Ethernet Rate	10/100 Mbit/s
Switching Method	Store and forward
PROFINET Role	IO device
Redundant Supply	Supported
Rated Supply	24 V DC
Maximum Current	0.35 A
Power Loss	8.4 W
Signaling Contact	24 V DC, 0.1 A maximum

ADDITIONAL PRODUCT DATA

Configuration Storage	C-PLUG optional
Ring Operation	Redundant ring supported
Operating Temperature	-40 to +60 °C
Management	Web and network management
Diagnostics	LED and error-signaling contact

OFFICIAL APPLICATIONS

- Machine Cells and Production Network Cabinets: Control network data exchange
- Auxiliary Controls and Electrical Switchgear Networks: Plant network communications
- Remote Pumping and Treatment Control Networks: Utility network communications

SYSTEM COMPATIBILITY

Match 6GK5224-0BA00-2AA3 to the installed SCALANCE X-200 managed switches, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Siemens official product documentation](#)

<https://support.industry.siemens.com/>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM