

OFFICIAL MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

6GK7343-1EX21-0XE0

Siemens official documentation for the exact article number

Source file: 6GK7343-1EX21-0XE0.pdf

The complete applicable Siemens Data Sheet follows this Amikon cover.

Product type designation



CP 343-1
Communications processor CP 343-1 for connection of SIMATIC S7-300 to Industrial Ethernet over PROFNET IO Controllers, ISO, TCP/IP and UDP, S7 communication, fetch/write, SEND/RECEIVE, with and without RFC1006 Diagnostic add-ons Multicast, chargeable Communication modules, SNMP diagnostics, Initialization via LAN, DHCP, NTP-CPU Sync, 10/100 MBit, only RJ45 connection

Transmission rate	
Transfer rate	
• at the 1st interface	10 ... 100 Mbit/s
Interfaces	
Number of interfaces / acc. to Industrial Ethernet	1
Number of electrical connections	
• at the 1st interface / acc. to Industrial Ethernet	1
• for power supply	1
Type of electrical connection	
• at the 1st interface / acc. to Industrial Ethernet	RJ45 port
• for power supply	2-pole plugable terminal block
design of the removable storage / C-PLUG	Yes
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage / 1 / from backplane bus	5 V
Supply voltage	24 V
Supply voltage / external	24 V

Supply voltage / external / at DC / Rated value	24 V
Relative positive tolerance / at DC / at 24 V	20 %
Relative negative tolerance / at DC / at 24 V	15 %
Consumed current • from external supply voltage / at DC / at 24 V / typical	0.2 A
Power loss [W]	5.8 W

Permitted ambient conditions

Ambient temperature • for vertical installation / during operation • for horizontally arranged busbars / during operation • during storage • during transport	0 ... 40 °C 0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-300 double width
Width	80 mm
Height	125 mm
Depth	120 mm
Net weight	0.22 kg
Mounting type • S7-300 rail mounting	Yes

Performance data / open communication

Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	16
Amount of data • as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum • as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum • as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum • as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte 8 Kibyte 8 Kibyte 2 Kibyte
Number of Multicast stations	16

Performance data / S7 communication

Number of possible connections / for S7 communication

- maximum

16

Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode

32

Performance data / PROFINET communication / as PN IO-Controller

Amount of data

- as user data for input variables / as PROFINET IO controller / maximum
- as user data for input variables / as PROFINET IO controller / maximum
- as user data for input variables per PN IO device / as PROFINET IO controller / maximum
- as user data for output variables per PN IO device / as PROFINET IO controller / maximum
- as user data for input variables per PN IO device / for each sub-module as PROFINET IO controller / maximum
- as user data for output variables per PN IO device / for each sub-module as PROFINET IO controller / maximum

1 Kibyte

1 Kibyte

1433 byte

1433 byte

240 byte

240 byte

Performance data / telecontrol

Protocol / is supported

- TCP/IP

Yes

Product functions / management, configuration

Product function / MIB support

Yes

Protocol / is supported

- SNMP v1
- DCP
- LLDP

Yes

Yes

No

Configuration software

- required

STEP 7 V5.3 SP3 or higher

Identification & maintenance function

- I&M0 - device-specific information
- I&M1 – higher-level designation/location designation

Yes

Yes

Product functions / Diagnosis

Product function / Web-based diagnostics

No

Product functions / switch

Product feature / Switch	No
Product functions / Redundancy	
Product function	
• Ring redundancy	No
Product functions / Security	
Product function	
• password protection for Web applications	No
• ACL - IP-based	Yes
• ACL - IP-based for PLC/routing	No
• switch-off of non-required services	No
• Blocking of communication via physical ports	No
• log file for unauthorized access	No
Product functions / Time	
Product function / SICLOCK support	Yes
Product function / pass on time synchronization	Yes
Protocol / is supported	
• NTP	Yes
Further Information / Internet Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
Security information	

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

02/13/2019 