

3300 XL 8 MM PROXIMITY TRANSDUCER SYSTEM

Product Data Sheet

330130-080-01-00

8 m armored extension cable

FUNCTION	FAMILY	ORIGIN	WEIGHT
8 m armored extension cable	3300 XL 8 mm Proximity	United States	0.82 kg

Bently Nevada 330130-080-01-00 is a armored extension cable for the 3300 XL 8 mm Proximity Transducer System. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Component Type	3300 XL standard extension cable
Cable Length	8.0 m (26.2 ft)
Cable Option	Armored cable
Agency Approval	Not required
Cable Construction	75 ohm triaxial, FEP insulated
Armor Material	AISI 302 or 304 stainless steel
Core Resistance	1.76 +/- 0.26 ohm
Jacket Resistance	0.53 +/- 0.11 ohm
Typical Capacitance	69.9 pF/m
Cable Temperature Range	-52 to +177 deg C

ADDITIONAL PRODUCT DATA

Typical Armored Mass	103 g/m
System Family	3300 XL 8 mm proximity transducer system
Linear Range	2.0 mm (80 mils)
Incremental Scale Factor	7.87 V/mm (200 mV/mil)
Frequency Response	0 to 10 kHz, +0/-3 dB

OFFICIAL APPLICATIONS

- Turbine monitoring: Shaft vibration and axial position measurement
- Compressor protection: Radial vibration and speed reference measurement
- Rotating equipment: Keyphasor phase reference and shaft position measurement

SYSTEM COMPATIBILITY

Match 330130-080-01-00 to the installed 3300 XL 8 mm Proximity Transducer System, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Bently Nevada 3300 XL 8 mm Proximity Transducer System Datasheet 141194 Rev. AM](#)

<https://dam.bakerhughes.com/m/23d2a1de24360b13/original/3300-XL-8mm-Proximity-Transducer-System-Datasheet-141194-pdf.pdf>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM