

3300 XL NSV PROXIMITY TRANSDUCER SYSTEMS

Product Data Sheet

330910-00-10-10-01-05

narrow sideview proximity probe

FUNCTION narrow sideview proximity probe	FAMILY 3300 XL NSv proximity transducer	ORIGIN United States	WEIGHT 0.28 kg
--	---	--------------------------------	--------------------------

3300 XL NSV Proximity Transducer 330910-00-10-10-01-05 is a narrow sideview proximity probe for the 3300 XL NSv proximity transducer systems. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Probe Thread	M10 × 1
Cable Armor	Stainless steel armor
Unthreaded Length	0 mm
Overall Case Length	100 mm
Total Cable Length	1.0 m
Connector Option	ClickLoc with protector
Approval Option	Multiple approvals
Recommended Gap	1.0 mm
Linear Range	0.25 to 1.75 mm
Scale Factor	7.87 V/mm

ADDITIONAL PRODUCT DATA

Frequency Response	0 to 10 kHz
Target Material	AISI 4140 steel
Cable Impedance	75 ohm coaxial
Probe Temperature	-34 to +177 °C

OFFICIAL APPLICATIONS

- Dryer rolls and stock preparation drives: Dryer roll bearing vibration measurement; Refiner drive shaft position tracking
- High-lift pumps and aeration blower trains: High-lift pump bearing vibration sensing; Aeration blower shaft condition measurement
- Propulsion shafts and auxiliary compressor trains: Propulsion bearing vibration measurement; Auxiliary compressor shaft position tracking

SYSTEM COMPATIBILITY

Match 330910-00-10-10-01-05 to the installed 3300 XL NSv proximity transducer systems, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Bently Nevada official manufacturer documentation](#)

<https://dam.bakerhughes.com/m/7a79b853504f738/original/3300-XL-NSv-Proximity-Transducer-System-Datasheet-147385-pdf.pdf>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM