

3300 XL 11 MM PROXIMITY TRANSDUCER SYSTEMS

Product Data Sheet

330710-00-060-10-02-00

eleven millimeter proximity probe

FUNCTION eleven millimeter proximity probe	FAMILY 3300 XL 11 mm proximity	ORIGIN United States	WEIGHT 0.35 kg
---	-----------------------------------	-------------------------	-------------------

3300 XL 11mm Proximity Transducer 330710-00-060-10-02-00 is a eleven millimeter proximity probe for the 3300 XL 11 mm proximity transducer systems. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Probe Thread	M16 × 1.5
Cable Armor	Stainless steel armor
Unthreaded Length	0 mm
Overall Case Length	60 mm
Total Cable Length	1.0 m
Connector Option	ClickLoc without protector
Approval Option	Not required
Measurement Range	Position and vibration
Frequency Response	0 to 8 kHz
Target Material	AISI 4140 steel

ADDITIONAL PRODUCT DATA

Connector System	Gold-plated ClickLoc
Cable Pull Strength	330 N
Terminal Type	SpringLoc
Probe Temperature	-51 to +177 °C

OFFICIAL APPLICATIONS

- Process compressors and reactor circulation pumps: Refrigeration compressor vibration measurement; Circulation pump bearing condition tracking
- Grinding mills and induced-draft fan trains: Mill pinion shaft vibration sensing; Furnace fan bearing condition measurement
- Dryer rolls and stock preparation drives: Dryer roll bearing vibration measurement; Refiner drive shaft position tracking

SYSTEM COMPATIBILITY

Match 330710-00-060-10-02-00 to the installed 3300 XL 11 mm proximity transducer systems, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Bently Nevada official manufacturer documentation](#)

<https://dam.bakerhughes.com/m/27a2d91f28aadd41/original/3300-XL-11mm-Proximity-Transducer-System-Datasheet-146256-pdf.pdf>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM