

SIMATIC S7-300 AUTOMATION SYSTEMS

Product Data Sheet

6ES7315-2AG10-0AB0

CPU 315-2 DP controller

FUNCTION CPU 315-2 DP controller	FAMILY SIMATIC S7-300 automation systems	ORIGIN Germany	WEIGHT 0.29 kg
--	--	--------------------------	--------------------------

S7-300 6ES7315-2AG10-0AB0 is a CPU 315-2 DP controller for the SIMATIC S7-300 automation systems. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

HW functional status	01
Firmware version	V2.6
Programming package	STEP 7 V5.2 + SP1 or higher with HW update
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2 A min.
Current consumption (rated value)	0.8 A
Current consumption (in no-load operation), typ.	60 mA
Inrush current, typ.	2.5 A
I ² t	0.5 A ² ·s

ADDITIONAL PRODUCT DATA

Power loss, typ.	2.5 W
integrated	128 kbyte; For program and data
Plug-in (MMC), max.	8 Mbyte
Data management on MMC (after last programming), min.	10 y
present	Yes; Guaranteed by MMC (maintenance-free)

OFFICIAL APPLICATIONS

- Machine and Conveyor Control Cabinets for Cpu 315-2 Dp Controller: Factory Control Systems Assembly machine I/O stations Production conveyor control panels
- Turbine Auxiliary Control Stations for Cpu 315-2 Dp Controller: Generation Control Systems Turbine auxiliary cabinets Generator cooling control panels
- Pumping and Treatment Control Stations for Cpu 315-2 Dp Controller: Utility Control Systems Booster pump PLC cabinets Filtration process control panels

SYSTEM COMPATIBILITY

Match 6ES7315-2AG10-0AB0 to the installed SIMATIC S7-300 automation systems, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Siemens official product data sheet](#)

Manufacturer official PDF

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM