

ROSEMOUNT TUPH PROCESS SENSORS

Product Data Sheet

396P-08-10-55

pH and ORP sensor

FUNCTION pH and ORP sensor	FAMILY Rosemount TUPH process sensors	ORIGIN United States	WEIGHT 0.50 kg
--------------------------------------	---	--------------------------------	--------------------------

Rosemount 396P-08-10-55 is a pH and ORP sensor for the Rosemount TUPH process sensors. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Measurement	pH or ORP
Cable Configuration	No preamplifier
Cable Length	10 ft (3.05 m)
Analyzer Option	Rosemount 56/1056/1057/1066/5081
Temperature Compensation	Pt-100 RTD
Maximum Pressure	150 psig (10.34 barg)
Maximum Temperature	100 °C
Process Threads	1 inch MNPT front and rear
Reference Design	Helical poisoning-resistant pathway
Solution Ground	Standard

ADDITIONAL PRODUCT DATA

Installation Angle	At least 10° above horizontal
--------------------	-------------------------------

OFFICIAL APPLICATIONS

- Pumping and filtration Ph And Orp Sensor applications: Utility Automation Systems
- Batching and packaging Ph And Orp Sensor applications: Production Control Systems
- Batch and utility suites Ph And Orp Sensor applications: Validated Control Systems

SYSTEM COMPATIBILITY

Match 396P-08-10-55 to the installed Rosemount TUpH process sensors, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Rosemount official manufacturer documentation](#)

Local official PDF: 396P-08-10-55.pdf

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM