

DELTA V S-SERIES TRADITIONAL I/O

Product Data Sheet

KJ3208X1-BA2

8-channel digital output card

FUNCTION 8-channel digital output card	FAMILY DeltaV S-series traditional I/O	ORIGIN United States	WEIGHT 0.40 kg
---	---	-------------------------	-------------------

DeltaV KJ3208X1-BA2 is a 8-channel digital output card for the DeltaV S-series traditional I/O. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Instruction Sheet	ATEX224
Local Bus Power	Field Circuit
Field Circuit	12 VDC at 150 mA
Ambient Temperature	-40°C to +70°C
Shock Rating	10g ½ Sinewave for 11msec
Vibration Rating	1mm Peak to Peak from 2 to 13.2Hz; 0.7g from 13.2 to 150Hz
Airborne Contaminants	ISA-S71.04 –1985 Airborne Contaminants Class G3
Relative Humidity	Position
Terminal Key Position	5 to 95% Non-Condensing
Insertion State	System power de-energized

ADDITIONAL PRODUCT DATA

Field Maintenance	No user-serviceable parts
Calibration	Not required

OFFICIAL APPLICATIONS

- Stock and paper machines 8-Channel Digital Output applications: Mill Production Systems
- Crushing and grinding 8-Channel Digital Output applications: Mineral Processing Systems
- Propulsion and utilities 8-Channel Digital Output applications: Marine Automation Systems

SYSTEM COMPATIBILITY

Match KJ3208X1-BA2 to the installed DeltaV S-series traditional I/O, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Emerson official manufacturer documentation](#)

Local official PDF: KJ3208X1-BA2.pdf

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM