

MANUFACTURER DOCUMENT PACKAGE

# Manufacturer's Manual

Reference package for procurement and maintenance review

DELTA V

## VE4035S2B1

REDUNDANT ANALOG OUTPUT PACKAGE

Used with the applicable DeltaV M-series traditional I/O configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: Emerson official manufacturer documentation

| Analog Output Cards and Termination Blocks                                                                                                  |              |
|---------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| Description                                                                                                                                 | Model Number |
| <b>8 Channels 4-20 mA, HART</b>                                                                                                             |              |
| Standard I/O Termination Block                                                                                                              | VE4005S2B1** |
| Redundant Standard I/O Termination Block                                                                                                    | VE4035S2B1** |
| Fused I/O Termination Block                                                                                                                 | VE4005S2B2** |
| 16-Pin Mass Termination Block                                                                                                               | VE4005S2B3** |
| <b>16 Channels 4-20 mA, HART, Plus Card</b>                                                                                                 |              |
| 16-Channel AO Terminal Block for Series 2 Plus                                                                                              | VE4005S2B4   |
| Redundant 16-Channel AO Terminal Block for Series 2 Plus                                                                                    | VE4035S2B4   |
| 48-pin AO Mass Termination Block for Series 2 Plus<br>(to be used with P+F HiC IS barriers and termination boards for DeltaV DCS)           | VE4005S2B5   |
| 48-pin AO Mass Termination Block for Series 2 Plus including 16-channel Analog Mass Connection Boards*                                      | VE4055S2B5   |
| Redundant 48-pin AO Mass Termination Block for Series 2 Plus<br>(to be used with P+F HiC IS barriers and termination boards for DeltaV DCS) | VE4035S2B5   |
| Redundant 48-pin AO Mass Termination Block for Series 2 Plus including 16-channel Analog Mass Connection Boards*                            | VE4085S2B5   |

\*For more details on the Mass Connection Boards and connection cables, please refer to the **M-series Mass Connection Solutions** PDS.

\*\*Supported on DeltaV v10.3.1 and later. If card will be used on earlier DeltaV versions, please request KJ3221X1-BA2.