

PACSYSTEMS RX3i CONTROLLERS

Product Data Sheet

IC695CPE302-BBAB

CPE302 programmable controller

FUNCTION	FAMILY	ORIGIN	WEIGHT
CPE302 programmable controller	PACSystems RX3i controllers	United States	0.80 kg

GE PACSystems RX3i IC695CPE302-BBAB is a CPE302 programmable controller for the PACSystems RX3i controllers. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

User Memory	2 MB
Discrete I/O	16K bits
Analog I/O	32K words
Ethernet Ports	2 switched 10/100/1000
USB Interface	1 x USB-A 2.0
Operating Temperature	0 to 60 °C
Backplane Slots	1
Processor Speed	1.1 GHz
Serial Protocols	ASCII and Modbus RTU
Remote I/O Devices	255 with PNC001

- Assembly and Inspection Manufacturing Cells: Factory Automation Systems
- Air Handling and Chilled Water Plants: Building Utility Systems
- Boiler and Turbine Auxiliary Systems: Plant Control Systems

Match IC695CPE302-BBAB to the installed PACSystems RX3i controllers, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[GE official manufacturer documentation](#)

Local official PDF: IC695CPE302-BBAB.pdf