

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

SIEMENS SIMATIC HMI

6AV3627-1JK00-0AX0

OP27 MONOCHROME OPERATOR PANEL

Used with the applicable SIMATIC HMI Operator Panels configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: Siemens official manufacturer documentation

*** SPARE PART*** OPERATOR PANEL OP27 STN
MONOCHROME LC DISPLAY

Display	
Design of display	STN, 8 gray scales
graphics-enabled	Yes
Screen diagonal	5.7 in
Color type	Grayscales
Resolution (pixels)	
• Horizontal image resolution	240 Pixel
• Vertical image resolution	320 Pixel
• Resolution (WxH in pixel)	240 x 320
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Control elements	Keys
Keyboard fonts	
• Membrane keyboard	Yes
— user-definable label membrane keys	Yes
• Function keys	24 function keys, 18 with LEDs
• Numeric/alphabetical input	Yes / Yes
— hexadecimal keyboard	Yes
• Multi-key operation	No
Touch operation	
• Design as touch screen	No
Connection type	
• Connection for mouse/keyboard/barcode reader	- / - / -
Installation type/mounting	
Mounting position	vertical
maximum permissible angle of inclination without external ventilation	35°
Supply voltage	
Type of supply voltage	18 V DC
UPS connectable (serial)	No
Input current	
Current consumption (rated value)	0.3 A

Power	
Power consumption, typ.	8 W
Processor	
Processor type	X86, 33 MHz
Drives	
Diskette drive	No
CD-ROM	No
Hard disk	No
Memory	
Type of memory	Flash / RAM
nutzbarer Speicher für Anwenderdaten	1 024 kbyte
Battery	
Backup battery	
• Backup battery	optional 3.6 V
• Backup time, min.	4 y
Type of output	
Info LED	Yes
Power LED	No
Time of day	
Clock	
• Type	Hardware clock, battery backup, synchronizable
• Hardware clock (real-time clock)	Yes
• Software clock	No
• retentive	Yes
• synchronizable	Yes
Interfaces	
Interfaces/bus type	1 x TTY, 2 x RS232, 1 x RS422, 1 x RS485 (max. 12 Mbit/s)
Number of RS 485 interfaces	1
• Transmission rate, max.	12 Mbit/s
USB port	No
PC card slot	1 x PC card slot
CF card slot	No
Special interfaces	No
Industrial Ethernet	
• Industrial Ethernet interface	No
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
Standards, approvals, certificates	

Certifications	PRS, FM Class I Div. 2, UL, EX Zone 22
cULus	No
RCM (formerly C-TICK)	No
Ambient conditions	
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	95 %
Operating systems	
Operating system	Rmos
Configuration	
Configuration software	
• Configuration tool	ProTool Version 3.1 or higher (to be ordered separately)
• 1. Configuration kit	ProTool
— Version	Version 3.1
— Configuration tool	ProTool
Dimensions	
Width of the housing front	296 mm
Height of housing front	192 mm
Overall depth	59 mm
Installation depth with direct key module	94 mm
Installation depth with Control Panel Interface	94 mm
Weights	
Weight (without packaging)	1.85 kg
Other	
free hotline	Yes
Warranty period	1 y
last modified:	13.08.2015