

SERIES 90-30 I/O

Product Data Sheet

IC693MDL753H

32-point DC output module

FUNCTION 32-point DC output module	FAMILY Series 90-30 I/O	ORIGIN United States	WEIGHT 0.80 kg
--	-----------------------------------	--------------------------------	--------------------------

GE 90-30 Series PLC IC693MDL753H is a 32-point DC output module for the Series 90-30 I/O. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Rated Voltage	12/24 V DC
Output Range	10.2 to 30 V DC
Discrete Outputs	32
Output Groups	4 groups of 8
Load per Point	0.5 A maximum
Module Load	4 A maximum per group
Output Drop	0.3 V maximum
Leakage Current	0.1 mA maximum
On Response	0.5 ms maximum after command
Off Response	0.5 ms maximum after de-energize

ADDITIONAL PRODUCT DATA

Inrush Current	4.78 A for 10 ms
Backplane Current	260 mA at 5 V DC

OFFICIAL APPLICATIONS

- Filling and packaging production halls for 32-point DC output module: Remote Station Systems
- Aeration and sludge treatment basins for 32-point DC output module: Energy Management Systems
- Turbine lubrication and cooling skids for 32-point DC output module: Drive Coordination Systems

SYSTEM COMPATIBILITY

Match IC693MDL753H to the installed Series 90-30 I/O, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[GE official manufacturer documentation](#)

<https://www.emerson.com/automation/>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM