

VERSAMAX DISCRETE I/O

Product Data Sheet

IC200MDL750L

32-point DC output module

FUNCTION 32-point DC output module	FAMILY VersaMax discrete I/O	ORIGIN United States	WEIGHT 0.80 kg
--	--	--------------------------------	--------------------------

GE VersaMax IC200MDL750L is a 32-point DC output module for the VersaMax discrete I/O. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Output Voltage	10.2 to 30 V DC
Nominal Voltage	12/24 V DC
Discrete Outputs	32
Output Groups	2 groups of 16
Load per Point	0.5 A maximum
Output Drop	0.3 V maximum
Leakage Current	0.5 mA maximum
On Response	0.2 ms maximum
Off Response	1.0 ms maximum
Backplane Current	90 mA at 5 V DC

- Warehouse sorting and conveyor zones for 32-point DC output module: Machine Control Systems
- Cargo handling and loading berths for 32-point DC output module: Facility Automation Systems
- Kiln feed and material processing lines for 32-point DC output module: Remote Station Systems

Match IC200MDL750L to the installed VersaMax discrete I/O, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[GE official manufacturer documentation](#)

<https://www.emerson.com/automation/>