

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

GE VERSAMAX

IC200PWR102K

120/240 V AC POWER SUPPLY

Used with the applicable VersaMax power supplies configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: GE official manufacturer documentation



Power Supplies

VersaMax Power Supply modules snap onto any VersaMax CPU or Network Interface Unit or onto a power supply booster carrier. Each power supply can be used as the main power source for modules in the I/O station, or as a source of supplemental power for larger I/O applications.

	IC200PWR001	IC200PWR002	IC200PWR011	IC200PWR012	IC200PWR101
Product Name	24 VDC Power Supply	24 VDC Power Supply with Expanded 3.3 V	24VDC Isolated Power Supply	24VDC Isolated Power Supply with Expanded 3.3 V	120/240 VAC Power Supply
Lifecycle Status	Active	Active	Active	Active	Active
Input Voltage	24 VDC	24 VDC	24 VDC	24 VDC	120/240 VAC
Output Voltage	5 VDC, 3.3 VDC	5 VDC, 3.3 VDC	5 VDC, 3.3 VDC	5 VDC, 3.3 VDC	5 VDC, 3.3 VDC
Extended Power	No	Yes	No	Yes	No
Input Power	11 W	11 W	11 W	11 W	27 VA
Isolated Power	No	No	Yes	Yes	N/A
Holdup Time	10 ms	10 ms	10 ms	10 ms	20 ms
Inrush Current	20 A @ 24 VDC; 25 A @ 30 VDC	20 A @ 24 VDC; 25 A @ 30 VDC	20 A @ 24 VDC; 25 A @ 30 VDC	20 A @ 24 VDC; 25 A @ 30 VDC	N/A
Protection	Short circuit, overload, reverse polarity	Short circuit, overload, reverse polarity	Short circuit, overload, reverse polarity	Short circuit, overload, reverse polarity	Short circuit, overload
Total Output Current	1.5 A maximum	1.5 A maximum	1.5 A maximum	1.5 A maximum	1.5 A maximum
3.3V Output Current	0.25 A maximum	1.0 A maximum	0.25 A maximum	1.0 A maximum	0.25 A maximum
5V Output Current	1.5 A minus the 3.3 V current used, maximum	1.5 A minus the 3.3 V current used, maximum	1.5 A minus the 3.3 V current used, maximum	1.5 A minus the 3.3 V current used, maximum	1.5 A minus the 3.3 V current used, maximum
Dimensions (W x H x D)	49 mm (1.93 in) x 133.4 mm (5.25 in) x 39 mm (1.54 in), not including the height of the carrier or the DIN-rail	49 mm (1.93 in) x 133.4 mm (5.25 in) x 39 mm (1.54 in), not including the height of the carrier or the DIN-rail	49 mm (1.93 in) x 133.4 mm (5.25 in) x 39 mm (1.54 in), not including the height of the carrier or the DIN-rail	49 mm (1.93 in) x 133.4 mm (5.25 in) x 39 mm (1.54 in), not including the height of the carrier or the DIN-rail	49 mm (1.93 in) x 133.4 mm (5.25 in) x 39 mm (1.54 in), not including the height of the carrier or the DIN-rail



Power Supplies

VersaMax Power Supply modules snap onto any VersaMax CPU or Network Interface Unit or onto a power supply booster carrier. Each power supply can be used as the main power source for modules in the I/O station, or as a source of supplemental power for larger I/O applications.

	IC200PWR102	IC200PWR201	IC200PWR202	IC200PWB001
	120/240 VAC Power Supply with Expanded 3.3 VDC	12 VDC Power Supply	12 VDC Power Supply with Expanded 3.3 VDC	VersaMax Power Supply Booster Carrier. Supplies power to all modules to the right of booster. Requires power supply.
Product Name				
Lifecycle Status	Active	Active	Active	Active
Input Voltage	120/240 VAC	9.6-15 VDC, 12 VDC nominal	9.6-15 VDC, 12 VDC nominal	N/A
Output Voltage	5 VDC, 3.3 VDC	5 VDC, 3.3 VDC	5 VDC, 3.3 VDC	N/A
Extended Power	Yes	No	Yes	N/A
Input Power	27 VA	11 W	11 W	N/A
Isolated Power	N/A	No	No	N/A
Holdup Time	20 ms	10 ms	10 ms	N/A
Inrush Current	N/A	25 A at 12 VDC; 30 A at 15 VDC	25 A at 12 VDC; 30 A at 15 VDC	N/A
Protection	Short circuit, overload	Short circuit, overload, reverse polarity	Short circuit, overload, reverse polarity	N/A
Total Output Current	1.5 A maximum	1.5 A maximum	1.5 A maximum	N/A
3.3V Output Current	1.0 A maximum	0.25 A maximum	1.0 A maximum	N/A
5V Output Current	1.5 A minus the 3.3 V current used, maximum	1.5 A minus the 3.3 V current used, maximum	1.5 A minus the 3.3 V current used, maximum	N/A
Dimensions (W x H x D)	49 mm (1.93 in) x 133.4 mm (5.25 in) x 39 mm (1.54 in), not including the height of the carrier or the DIN-rail	49 mm (1.93 in) x 133.4 mm (5.25 in) x 39 mm (1.54 in), not including the height of the carrier or the DIN-rail	49 mm (1.93 in) x 133.4 mm (5.25 in) x 39 mm (1.54 in), not including the height of the carrier or the DIN-rail	66.8 mm (2.63 in) x 133.4 mm (5.25 in) x 70 mm (2.75 in), not including the height of DIN-rail