

FOXBORO I/A SERIES DCS

Product Data Sheet

FBM206 P0916CQ

Channel Isolated 8 Input,Pulse

FUNCTION Channel Isolated 8 Input,Pulse	FAMILY Foxboro I/A Series DCS	ORIGIN United States	WEIGHT 0.30 kg
---	---	--------------------------------	--------------------------

Foxboro FBM206 P0916CQ is a Channel Isolated 8 Input,Pulse for the Foxboro I/A Series DCS. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

TEMPERATURE	-40 to +70 deg C (-40 to +158 deg F)
ALTITUDE	-300 to +12,000 m (-1,000 to +40,000 ft)
LINEARITY ERROR	+/-0.025% of span (monotonic)
I/O Function	Pulse input
Channel Configuration	8 inputs
Signal Range	10 Hz to 25 kHz
Module Fieldbus	Redundant 2 Mbps
Supply Voltage	24 V DC
Mounting	Modular baseplate
Operating Temperature	-20 to +70 deg C

ADDITIONAL PRODUCT DATA

Module Series	200 Series FBM
System Platform	Foxboro DCS

OFFICIAL APPLICATIONS

- Turbine auxiliary I/O cabinets: Plant Interface Systems
- Compressor skid signal processing: Process I/O Systems
- Reactor instrumentation control panels: Distributed I/O Systems

SYSTEM COMPATIBILITY

Match FBM206 P0916CQ to the installed Foxboro I/A Series DCS, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Amikon model-specific product data sheet](#)

<https://www.amikong.com/Foxboro-c475.html>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM