

FOXBORO I/A SERIES DCS

Product Data Sheet

FBM216b

Redundant Ready HART Inputs

FUNCTION	FAMILY	ORIGIN	WEIGHT
Redundant Ready HART Inputs	Foxboro I/A Series DCS	United States	0.32 kg

Foxboro FBM216b is a Redundant Ready HART Inputs for the Foxboro I/A Series DCS. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

I/O Function	Redundant HART input
Channel Configuration	8 inputs
Signal Range	4 to 20 mA with HART
Module Fieldbus	Redundant 2 Mbps
Supply Voltage	24 V DC
Mounting	Modular baseplate
Operating Temperature	-20 to +70 deg C
Module Series	200 Series FBM
System Platform	Foxboro DCS

- Compressor skid signal processing: Process I/O Systems
- Reactor instrumentation control panels: Distributed I/O Systems
- Turbine auxiliary I/O cabinets: Plant Interface Systems

Match FBM216b to the installed Foxboro I/A Series DCS, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[Schneider Electric / Foxboro official product specification](#)

<https://paresource.se.com/iaseries/pss/41h2/41h2s216.pdf>