

FOXBORO PROCESS AUTOMATION SYSTEMS

Product Data Sheet

AD908AA

D Cable Plus 1 meter

FUNCTION	FAMILY	ORIGIN	WEIGHT
D Cable Plus 1 meter	Foxboro process automation systems	United States	0.20 kg

Foxboro AD908AA is a D Cable Plus 1 meter for the Foxboro process automation systems. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Length	1 m
Conductors	26 AWG
Voltage Rating	300 V AC
Operating Temp	-40 deg C to +70 deg C
Storage Temp	-55 deg C to +85 deg C
Humidity	0 - 95 % RH non-condensing
Assembly Type	Termination cable
System Platform	Foxboro I/A Series
Connection A	FBM interface
Connection B	Termination assembly

ADDITIONAL PRODUCT DATA

Cable Type	Industrial multicore
Installation	Control cabinet
Shielding	Industrial screened cable
Termination	Pre-terminated connectors
Conductor Size	26AWG

OFFICIAL APPLICATIONS

- Compressor control cabinet interconnections: Field Wiring Systems
- Reactor unit field termination panels: Process Interface Systems
- Turbine auxiliary control cabinets: Plant Cabling Systems

SYSTEM COMPATIBILITY

Match AD908AA to the installed Foxboro process automation systems, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Amikon model-specific product data sheet](#)

<https://www.amikong.com/Foxboro-c475.html>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM