

SIMATIC S7-300 COMMUNICATION

Product Data Sheet

6ES7341-1AH01-0AE0

CP 341 RS232 processor

FUNCTION CP 341 RS232 processor	FAMILY SIMATIC S7-300 communication	ORIGIN Germany	WEIGHT 0.26 kg
---	---	--------------------------	--------------------------

S7-300 6ES7341-1AH01-0AE0 is a CP 341 RS232 processor for the SIMATIC S7-300 communication. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

24 V Dc	Yes
Supply Voltage	200 mA
From Backplane Bus 5 V Dc, Max.	70 mA
Power Loss	4.8 W
Number of Interfaces	1; Isolated
Transmission Rate, Min.	0.3 kbit/s
Transmission Rate, Max.	76.8 kbit/s
Cable Length, Max.	15 m
Connector Type	9-pin sub D connector
Fb Length In Ram, Max.	5 500 byte; Data communication, sending and receiving

Power Supply

3 screw-type terminals: L+, M, GND

- Pumping and Filtration Plants: Utility Automation Systems
- Compression and Pipeline Stations: Hydrocarbon Control Systems
- Stock and Paper Machines: Mill Production Systems

Match 6ES7341-1AH01-0AE0 to the installed SIMATIC S7-300 communication, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[Siemens official product documentation](#)

Local manufacturer PDF: 6ES7341-1AH01-0AE0.pdf

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM