

SIMATIC S7-400 COMMUNICATION

Product Data Sheet

6GK7443-5DX04-0XE0

PROFIBUS communication processor

FUNCTION PROFIBUS communication processor	FAMILY SIMATIC S7-400 communication	ORIGIN Germany	WEIGHT 0.66 kg
---	---	--------------------------	--------------------------

Siemens Simatic Net 6GK7443-5DX04-0XE0 is a PROFIBUS communication processor for the SIMATIC S7-400 communication. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Transfer Rate	9.6 kbit/s ... 12 Mbit/s
Number of Interfaces	0
Supply Voltage	DC
At 5 V	5 %
From Backplane Bus	1 A
Power Loss	5 W
During Operation	0 ... 60 °C
Storage Temperature	40 ... +70 °C
Relative Humidity	95 %
Protection Degree	IP20

ADDITIONAL PRODUCT DATA

Module Format	Compact module S7-400 single width
Per Cpu	14
Number of Possible Connections	32
As User Data Per Connection	240 byte
Dpv1	Yes

OFFICIAL APPLICATIONS

- Boiler and Turbine Control Stations: Generation Control Systems
- Reactor and Separation Units: Process Control Systems
- Crushing and Grinding Plants: Mineral Processing Systems

SYSTEM COMPATIBILITY

Match 6GK7443-5DX04-0XE0 to the installed SIMATIC S7-400 communication, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Siemens official product documentation](#)

Local manufacturer PDF: 6GK7443-5DX04-0XE0.pdf

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM