

SINAMICS S210 DRIVES

Product Data Sheet

6SL3210-5HE11-5UF0

SINAMICS S210 servo drive

FUNCTION SINAMICS S210 servo drive	FAMILY SINAMICS S210 drives	ORIGIN Germany	WEIGHT 3.300 kg
--	---------------------------------------	--------------------------	---------------------------

Siemens SINAMICS 6SL3210-5HE11-5UF0 is a SINAMICS S210 servo drive for the SINAMICS S210 drives. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Input Phases	3 AC
Input Voltage	200 to 480 V $\pm 10\%$
Line Frequency	45 to 66 Hz
Rated Input Current	6.0 A
Inrush Current	8.6 A
Rated Output Power	1.50 kW at 400 V
Rated Output Current	5.0 A
Maximum Output Current	19.0 A
Output Frequency	0 to 550 Hz
Pulse Frequency	8 kHz

ADDITIONAL PRODUCT DATA

Protection Degree	IP20
Frame Size	B

OFFICIAL APPLICATIONS

- Stock and Paper Machines: Mill Production Systems
- Pumping and Filtration Plants: Utility Automation Systems
- Compression and Pipeline Stations: Hydrocarbon Control Systems

SYSTEM COMPATIBILITY

Match 6SL3210-5HE11-5UF0 to the installed SINAMICS S210 drives, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Siemens official product documentation](#)

Local manufacturer PDF: 6SL3210-5HE11-5UF0.pdf

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM