

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

SIEMENS SINAMICS

6SL3210-5HE11-5UF0

SINAMICS S210 SERVO DRIVE

Used with the applicable SINAMICS S210 drives configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: Siemens official product documentation

MLFB-Ordering data

6SL3210-5HE11-5UF0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		Communication	
Input		Communication	PROFINET
Number of phases	3 AC	Ambient conditions	
Line voltage	200 ... 480 V ± 10 %	Installation altitude	1000 m (3280.84 ft)
Line frequency	45 ... 66 Hz	Cooling	Air cooling using an integrated fan
Rated current	6.0 A	Ambient temperature during	
Inrush current	8.6 A	Operation	0 ... 50 °C (32 ... 122 °F)
Output			Better than class 3K3, in acc. with EN 60721-3-3: 2002, without derating
Number of phases	3 AC	Transport	-40 ... 70 °C (-40 ... 158 °F)
Rated power (at 400V)	1.50 kW (2.04 hp)		Class 2K4, in acc. with EN 60721-3-2: 1997, in transport packaging
Rated current I_N	5.0 A	Storage	-25 ... 55 °C (-13 ... 131 °F)
Max. output current	19.0 A		Class 1K4, in acc. with EN 60721-3-1: 1997, in product packaging
Pulse frequency	8 kHz	Relative humidity during	
Output frequency for servo control	0 ... 550 Hz	Max. operation	95 %
Electronics power supply			RH, condensation not permitted
Voltage	24 V -15 % ... +20 %	Transport, max.	95 %
Current demand, max.	1.0 A		at 40 °C (104 °F)
		Bearing, max.	95 %

MLFB-Ordering data

6SL3210-5HE11-5UF0



Figure similar

Inputs / outputs	Connections																				
Standard digital inputs <table> <tr> <td>Number</td><td>5</td></tr> <tr> <td></td><td>of which 2 for F-DI</td></tr> </table>	Number	5		of which 2 for F-DI	Line side <table> <tr> <td>Version</td><td>push-in spring-type terminals</td></tr> <tr> <td>Conductor cross-section</td><td>0.75 ... 6.00 mm² / 18 ... 10 AWG</td></tr> </table>	Version	push-in spring-type terminals	Conductor cross-section	0.75 ... 6.00 mm² / 18 ... 10 AWG												
Number	5																				
	of which 2 for F-DI																				
Version	push-in spring-type terminals																				
Conductor cross-section	0.75 ... 6.00 mm² / 18 ... 10 AWG																				
Fail-safe digital inputs <table> <tr> <td>Number</td><td>1</td></tr> <tr> <td></td><td>Can only be used for STO/SS1</td></tr> </table>	Number	1		Can only be used for STO/SS1	Motor end <table> <tr> <td>Version</td><td>push-in spring-type terminals</td></tr> <tr> <td>Conductor cross-section</td><td>0.75 ... 6.00 mm² / 18 ... 10 AWG</td></tr> </table>	Version	push-in spring-type terminals	Conductor cross-section	0.75 ... 6.00 mm² / 18 ... 10 AWG												
Number	1																				
	Can only be used for STO/SS1																				
Version	push-in spring-type terminals																				
Conductor cross-section	0.75 ... 6.00 mm² / 18 ... 10 AWG																				
Mechanical data																					
Dimensions <table> <tr> <td>Width</td><td>70.0 mm (2.76 in)</td></tr> <tr> <td>Height without shield plate</td><td>322.0 mm (12.68 in)</td></tr> <tr> <td>Depth</td><td>223.0 mm (8.78 in)</td></tr> <tr> <td>Mounting position</td><td>vertical wall mounting</td></tr> <tr> <td>Degree of protection</td><td>IP20 / UL open type</td></tr> <tr> <td>Frame size</td><td>FSB</td></tr> <tr> <td>Net weight</td><td>3.30 kg (7.28 lb)</td></tr> </table>	Width	70.0 mm (2.76 in)	Height without shield plate	322.0 mm (12.68 in)	Depth	223.0 mm (8.78 in)	Mounting position	vertical wall mounting	Degree of protection	IP20 / UL open type	Frame size	FSB	Net weight	3.30 kg (7.28 lb)	DC link (for braking resistor) <table> <tr> <td>Version</td><td>push-in spring-type terminals</td></tr> <tr> <td>Conductor cross-section</td><td>0.75 ... 6.00 mm² / 18 ... 10 AWG</td></tr> <tr> <td>Cable length</td><td>10 m (32.81 ft)</td></tr> </table>	Version	push-in spring-type terminals	Conductor cross-section	0.75 ... 6.00 mm² / 18 ... 10 AWG	Cable length	10 m (32.81 ft)
Width	70.0 mm (2.76 in)																				
Height without shield plate	322.0 mm (12.68 in)																				
Depth	223.0 mm (8.78 in)																				
Mounting position	vertical wall mounting																				
Degree of protection	IP20 / UL open type																				
Frame size	FSB																				
Net weight	3.30 kg (7.28 lb)																				
Version	push-in spring-type terminals																				
Conductor cross-section	0.75 ... 6.00 mm² / 18 ... 10 AWG																				
Cable length	10 m (32.81 ft)																				
	PE connection <table> <tr> <td>Version</td><td>M4 screw studs</td></tr> </table>	Version	M4 screw studs																		
Version	M4 screw studs																				
	Max. motor cable length <table> <tr> <td>Shielded</td><td>50 m (164.04 ft)</td></tr> </table>	Shielded	50 m (164.04 ft)																		
Shielded	50 m (164.04 ft)																				
	Standards																				
	<table> <tr> <td>Compliance with standards</td><td>CE, cULus, RCM, KC, EAC</td></tr> </table>	Compliance with standards	CE, cULus, RCM, KC, EAC																		
Compliance with standards	CE, cULus, RCM, KC, EAC																				
	<table> <tr> <td>CE marking</td><td>Low-voltage directive 2006/95/EC</td></tr> </table>	CE marking	Low-voltage directive 2006/95/EC																		
CE marking	Low-voltage directive 2006/95/EC																				
	<table> <tr> <td>Verification of suitability for fail-safety</td><td>SIL 2 in acc. with IEC 61508 parts 1-3 (2010) and IEC 61800-5-2 (2016), PL d in acc. with ISO 13849 part 1 (2015), Category 3 in acc. with IEC 60204 (2007)</td></tr> </table>	Verification of suitability for fail-safety	SIL 2 in acc. with IEC 61508 parts 1-3 (2010) and IEC 61800-5-2 (2016), PL d in acc. with ISO 13849 part 1 (2015), Category 3 in acc. with IEC 60204 (2007)																		
Verification of suitability for fail-safety	SIL 2 in acc. with IEC 61508 parts 1-3 (2010) and IEC 61800-5-2 (2016), PL d in acc. with ISO 13849 part 1 (2015), Category 3 in acc. with IEC 60204 (2007)																				