

SERIES 90-30 ANALOG I/O

Product Data Sheet

IC693ALG223-FA

16-channel current input module

FUNCTION	FAMILY	ORIGIN	WEIGHT
16-channel current input module	Series 90-30 analog I/O	United States	0.80 kg

GE 90-30 Series PLC IC693ALG223-FA is a 16-channel current input module for the Series 90-30 analog I/O. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Analog Inputs	16 single-ended
Input Ranges	0–20 mA; 4–20 mA
Resolution	15 bits
Update Rate	13 ms maximum
Input Impedance	250 Ω
Channel Isolation	Not isolated
Field Isolation	250 V AC continuous
Isolation Test	1,500 V AC for 1 minute
Backplane Current	120 mA at 5 V DC
External Supply	20 to 30 V DC

ADDITIONAL PRODUCT DATA

Alarm Limits	High and low alarms
Terminal Block	36 terminals

OFFICIAL APPLICATIONS

- Filling and packaging production halls: Remote Station Systems
- Aeration and sludge treatment basins: Energy Management Systems
- Turbine lubrication and cooling skids: Drive Coordination Systems

SYSTEM COMPATIBILITY

Match IC693ALG223-FA to the installed Series 90-30 analog I/O, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[GE official manufacturer documentation](#)

<https://www.emerson.com/automation/>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM