

PACSYSTEMS RX3i COMMUNICATIONS

Product Data Sheet

IC695CMM004

four-port serial communications module

FUNCTION	FAMILY	ORIGIN	WEIGHT
four-port serial communications module	PACSystems RX3i communications	United States	0.80 kg

GE PACSystems RX3i IC695CMM004 is a four-port serial communications module for the PACSystems RX3i communications. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Serial Ports	4 isolated ports
Port Standards	RS-232, RS-485 and RS-422
Baud Rates	300 to 115,200 bit/s
Protocols	Modbus RTU master/slave and serial I/O
Port Isolation	Independent isolation
Connector	Two 36-pin terminal blocks
Backplane Type	RX3i universal
Hot Insertion	Supported
Configuration	Machine Edition
Module Width	Single slot

- Paint shop and body transfer lines: Process Control Systems
- Ore conveying and screening stations: Plant Utility Systems
- Pulp washing and bleaching plants: Equipment Monitoring Systems

Match IC695CMM004 to the installed PACSystems RX3i communications, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[GE official manufacturer documentation](#)

<https://www.emerson.com/automation/>