

PACSYSTEMS RX3i COMMUNICATIONS

Product Data Sheet

IC695PBS301

PROFIBUS slave module

FUNCTION PROFIBUS slave module	FAMILY PACSystems RX3i communications	ORIGIN United States	WEIGHT 0.80 kg
--	---	--------------------------------	--------------------------

GE PACSystems RX3i IC695PBS301 is a PROFIBUS slave module for the PACSystems RX3i communications. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Protocol	PROFIBUS DP-V1 slave
Network Port	1 PROFIBUS port
Baud Rate	9.6 kbit/s to 12 Mbit/s
Input Data	244 bytes maximum
Connector	9-pin D-sub
Node Address	0 to 125
Backplane Current	440 mA at 3.3 V DC
Module Width	Single slot

- Fermentation and bottling process lines: Material Handling Systems
- Filtration and disinfection stations: Safety Interlock Systems
- Generator cooling and switchyard systems: Machine Control Systems

Match IC695PBS301 to the installed PACSystems RX3i communications, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[GE official manufacturer documentation](#)

<https://www.emerson.com/automation/>