

PACSYSTEMS RX3i CONTROLLERS

Product Data Sheet

IC695CPE330-ABAF

CPE330 programmable controller

FUNCTION	FAMILY	ORIGIN	WEIGHT
CPE330 programmable controller	PACSystems RX3i controllers	United States	1.20 kg

GE PACSystems RX3i IC695CPE330-ABAF is a CPE330 programmable controller for the PACSystems RX3i controllers. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

User Memory	64 MB
Processor	1 GHz
Boolean Scan	0.047 ms per K
Ethernet Ports	4 switched 10/100/1000
USB Interface	USB-A 2.0 host
Serial Interface	RS-232
Backplane Slots	2
Operating Temperature	0 to 60 °C
Energy Pack	IC695ACC402

ADDITIONAL PRODUCT DATA

OFFICIAL APPLICATIONS

- Compression and pipeline terminals: Equipment Monitoring Systems
- Blending and reactor process units: Production Interface Systems
- Clean utility production suites: Material Handling Systems

SYSTEM COMPATIBILITY

Match IC695CPE330-ABAF to the installed PACSystems RX3i controllers, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[GE official manufacturer documentation](#)

<https://www.emerson.com/automation/>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM