

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

GE 90-30 SERIES PLC

IC693CPU372-AE

CPU 372 ETHERNET CONTROLLER

Used with the applicable Series 90-30 controllers configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: IC693CPU372-AE.pdf



CPU

For entry-level applications with low I/O counts, the CPU is embedded into the backplane, making all slots available for I/O. These modules are compatible with advanced modules such as Ethernet, various bus modules, and control. Mid-range CPU models are modular and come in various memory sizes, performance capability and increased functionality such as overrides, battery-backed clock and Programmable Coprocessor module support. The high-performance CPUs are based on the latest 386EX processor for fast computation and high throughput. They can handle up to 4,096 I/O and start at 32K of memory and are programmable in a number of standard languages.

	IC693CPU370	IC693CPU372	IC693CPU374 PLUS
Product Name	CPU (Model 370). Requires High Capacity Power Supply	CPU (Model 372 with built-in 10/100 Mbps Ethernet and WEB Enabled). Requires High Capacity Power Supply	CPU (Model 374 PLUS with built-in 10/100 Mbps Ethernet and Web Enabled). Requires High Capacity Power Supply
Lifecycle Status	Active	Active	Active
Module Type	CPU Module	CPU Module	CPU Module
Boolean Execution Speed (ms/K)	0.15	0.15	0.15
User Logic Memory (K bytes)	240	120	240
Real Time Clock	Yes	Yes	Yes
I/O Discrete Points	4096	4096	4096
I/O Analog Points	2048 In / 512 Out	2048 In / 512 Out	2048 In / 512 Out
Type of Memory Storage	RAM, Flash	RAM, Flash	RAM, Flash
Processor Speed (MHz)	133Mhz	133Mhz	133Mhz
Built-in Communication Ports	One RS-485 port on power supply. Supports SNP	One RS-485 port on power supply. Supports SNP and two Ethernet ports; (one IP address) on CPU, 10/100 Mbps built-in switch, SRTP - channels (Producer and Consumer); EGD, Modbus TCP Client/Server and Web Diagnostics Support	One RS-485 port on power supply. Supports SNP and two Ethernet ports; (one IP address) on CPU, 10/100 Mbps built-in switch, SRTP - channels (Producer and Consumer); EGD, Modbus TCP Client/Server and Web Diagnostics Support
Total Number of Racks	8	8	8
Communications Option Modules	Serial-SNP, SNPX, RTU and CCM, LAN-Genius, Ethernet SRTP and Ethernet Modbus TCP Client/Server	Serial-SNP, SNPX, RTU and CCM, LAN-Genius, Ethernet SRTP and Ethernet Modbus TCP Client/Server	Serial-SNP, SNPX, RTU and CCM, LAN-Genius, Ethernet SRTP and Ethernet Modbus TCP Client/Server
Field Busses/Device Networks	Ethernet, Genius, Profibus-DP, DeviceNet, Interbus-S, CsCAN	Ethernet, Genius, Profibus-DP, DeviceNet, Interbus-S, CsCAN	Ethernet, Genius, Profibus-DP, DeviceNet, Interbus-S, CsCAN
Software Programming Support	Proficy Logic Developer - Machine Edition	Proficy Logic Developer - Machine Edition	Proficy Logic Developer -Machine Edition
Internal Power Used	1.4 Amps @ 5 VDC	1.4 Amps @ 5 VDC	1.4 Amps @ 5 VDC