

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

GE 90-30 SERIES PLC

IC693CPU370

CPU 370 CONTROLLER MODULE

Used with the applicable Series 90-30 controllers configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: GE official manufacturer documentation



CPU's

The high-performance CPU is based on the latest technology processor with fast computation and high throughput. The controller can manage up to 32K of I/O in a number of standard languages. The powerful CPU enables complex applications to be easily solved with the high performance processor and up to 64 Mbytes of user memory. The RX3i supports multiple IEC languages and C programming to give you program flexibility. The RX3i increases machine cycle times, reduces downtime with its extensive diagnostics and hot swap capability, and enables you to store large amounts of data to reduce external hardware cost.

	IC695CPE305	IC695CPE310	IC695CPU320	IC695CPU315
Product Name	RX3i CPU with built-in USB Master port, Ethernet port and serial port	RX3i CPU with built-in USB Master port, Ethernet port and 2 serial ports	RX3i CPU with two built-in serial ports	RX3i CPU with two built-in serial ports
Lifecycle Status	Active	Active	Active	Active
Module Type	Controller	Controller	Controller	Controller
Backplane Support	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.
Boolean Execution Speed (ms/K)	.072	.072	0.047	0.047
User Logic Memory	5Meg bytes	10Meg bytes	64Mega bytes	20Meg bytes
Battery Backed Real Time Clock	Yes	Yes	Yes	Yes
Dynamic Data Back-up	Energy Pack Support (Battery-less Backup)	Energy Pack Support (Battery-less Backup)	Battery Backup only	Battery Backup only
I/O Discrete Points	32K	32K	32K	32K
I/O Analog Points	32K	32K	32K	32K
Type of Memory Storage	SRAM, Flash	SRAM, Flash	SRAM, Flash	SRAM, Flash
Processor Speed (MHz)	1.1GHz	1.1GHz	1GHz	1GHz
USB -A 2.0 Master Port	Yes. CPU application upload/download to a Thumb Drive or Smart Phone	Yes. CPU application upload/download to a Thumb Drive or Smart Phone	No	No
Built-in Ethernet Ports	One RJ-45 port, 10/100Mbaud. SRTP support for programmer only	One RJ-45 port, 10/100Mbaud. SRTP support for programmer only		
Built-in Serial Ports	One RS-232 port. Supports SNP, Serial I/O, Modbus Slave and Modbus Master (Application code)	One RS-485 port and one RS-232 port. Supports SNP, Serial I/O, Modbus Slave and Modbus Master (Application code)	One RS-485 port and one RS-232 port. Supports SNP, Serial I/O, Modbus Slave and Modbus Master (Application code)	One RS-485 port and one RS-232 port. Supports SNP, Serial I/O, Modbus Slave and Modbus Master (Application code)
Total Number of Local Racks	8	8	8	8
Communications Options	Serial, Genius, CMX (Reflective Memory), Ethernet			
Field Busses/Device Networks	Ethernet (Profinet, Ethernet Global Data, Channels, Modbus TCP Server and Client), Genius, Profibus DP, DeviceNet			
Software Programming Support	Proficy Machine Edition Logic Developer Professional edition 7.0 SIM 3 or above	Proficy Machine Edition Logic Developer Professional edition 7.0 SIM 3 or above	Proficy Machine Edition Logic Developer Professional edition 5.6 or above	Proficy Machine Edition Logic Developer Professional edition 5.6 or above
Program Languages Supported	Ladder Logic, Structured Text, C, Function Block Diagram	Ladder Logic, Structured Text, C, Function Block Diagram	Ladder Logic, Structured Text, C, Function Block Diagram	Ladder Logic, Structured Text, C, Function Block Diagram
Internal Power Used	+3.3 VDC: 1.0 A +5 VDC: 1.0 A (up to 1.5 A if USB is fully loaded with 0.5 A) +24 VDC: 0.5A at startup, 0.1 A during run time (Applies only if Energy Pack is connected to the CPE305.)	+3.3 VDC: 1.0 A +5 VDC: 1.0 A (up to 1.5 A if USB is fully loaded with 0.5 A) +24 VDC: 0.5A at startup, 0.1 A during run time (Applies only if Energy Pack is connected to the CPE305.)	1750 mA @ 3.3 VDC; 1200 mA @ 5 VDC	1750 mA @ 3.3VDC; 1200 mA @ 5VDC (Check Data sheet)
Number of Slots Module Occupies on Backplane	1	2	2	2



CPU's

For entry-level applications with low I/O counts, the CPU is embedded into the backplane, making all slots available for I/O. These modules are compatible with advanced modules such as Ethernet, various bus modules, and control. Mid-range CPU models are modular and come in various memory sizes, performance capability and increased functionality such as overrides, battery-backed clock and Programmable Coprocessor module support. The high-performance CPUs are based on the latest 386EX processor for fast computation and high throughput. They can handle up to 4,096 I/O and start at 32K of memory and are programmable in a number of standard languages.

	IC693CPU311	IC693CPU313	IC693CPU323	IC693CPU350	IC693CPU360
Product Name	5-slot Baseplate (Model 311)	5-slot Baseplate (Model 313)	10-slot Baseplate (Model 323)	CPU (Model 350)	CPU (Model 360)
Lifecycle Status	Active	Active	Active	Active	Active
Module Type	I/O Base with built-in CPU	I/O Base with built-in CPU	I/O Base with built-in CPU	CPU Module	CPU Module
Boolean Execution Speed (ms/K)	18	0.6	0.6	0.22	0.22
User Logic Memory (K bytes)	6	12	12	74	240
Real Time Clock	No	No	No	Yes	Yes
I/O Discrete Points	160	160	320	4096	4096
I/O Analog Points	64 In / 32 Out	64 In / 32 Out	64 In / 32 Out	2048 In / 512 Out	2048 In / 512 Out
Type of Memory Storage	RAM, EPROM, EEPROM	RAM, EPROM, EEPROM	RAM, EPROM, EEPROM	RAM, Flash	RAM, Flash
Processor Speed (MHz)	N/A	N/A	N/A	N/A	N/A
Built-in Communication Ports	One RS-485 port on power supply. Supports SNP	One RS-485 port on power supply. Supports SNP	One RS-485 port on power supply. Supports SNP	One RS-485 port on power supply. Supports SNP	One RS-485 port on power supply. Supports SNP
Total Number of Racks	1 (CPU built in)	1 (CPU built in)	1 (CPU built in)	8	8
Communications Option Modules	Serial-SNP and RTU, LAN-Genius, Ethernet SRTP and Ethernet Modbus TCP	Serial-SNP and RTU, LAN-Genius, Ethernet SRTP and Ethernet Modbus TCP	Serial-SNP and RTU, LAN-Genius, Ethernet SRTP and Ethernet Modbus TCP	Serial-SNP, SNP-X, RTU and CCM, LAN-Genius, Ethernet SRTP and Ethernet Modbus TCP	Serial-SNP, SNP-X, RTU and CCM, LAN-Genius, Ethernet SRTP and Ethernet Modbus TCP
Field Busses/Device Networks	Ethernet, Genius, Profibus-DP, DeviceNet, Interbus-S, CsCAN	Ethernet, Genius, Profibus-DP, DeviceNet, Interbus-S, CsCAN	Ethernet, Genius, Profibus-DP, DeviceNet, Interbus-S, CsCAN	Ethernet, Genius, Profibus-DP, DeviceNet, Interbus-S, CsCAN	Ethernet, Genius, Profibus-DP, DeviceNet, Interbus-S, CsCAN
Software Programming Support	Logicmaster (DOS), VersaPro (Windows), Proficy Logic Developer - Machine Edition	Logicmaster (DOS), VersaPro (Windows), Proficy Logic Developer - Machine Edition	Logicmaster (DOS), VersaPro (Windows), Proficy Logic Developer - Machine Edition	Logicmaster (DOS), VersaPro (Windows), Proficy Logic Developer - Machine Edition	Logicmaster (DOS), VersaPro (Windows), Proficy Logic Developer - Machine Edition
Internal Power Used	410 mA @ 5 VDC	430 mA @ 5 VDC	430 mA @ 5 VDC	670 mA @ 5 VDC	670 mA @ 5 VDC



CPU

For entry-level applications with low I/O counts, the CPU is embedded into the backplane, making all slots available for I/O. These modules are compatible with advanced modules such as Ethernet, various bus modules, and control. Mid-range CPU models are modular and come in various memory sizes, performance capability and increased functionality such as overrides, battery-backed clock and Programmable Coprocessor module support. The high-performance CPUs are based on the latest 386EX processor for fast computation and high throughput. They can handle up to 4,096 I/O and start at 32K of memory and are programmable in a number of standard languages.

	IC693CPU370	IC693CPU372	IC693CPU374 PLUS
Product Name	CPU (Model 370). Requires High Capacity Power Supply	CPU (Model 372 with built-in 10/100 Mbps Ethernet and WEB Enabled). Requires High Capacity Power Supply	CPU (Model 374 PLUS with built-in 10/100 Mbps Ethernet and Web Enabled). Requires High Capacity Power Supply
Lifecycle Status	Active	Active	Active
Module Type	CPU Module	CPU Module	CPU Module
Boolean Execution Speed (ms/K)	0.15	0.15	0.15
User Logic Memory (K bytes)	240	120	240
Real Time Clock	Yes	Yes	Yes
I/O Discrete Points	4096	4096	4096
I/O Analog Points	2048 In / 512 Out	2048 In / 512 Out	2048 In / 512 Out
Type of Memory Storage	RAM, Flash	RAM, Flash	RAM, Flash
Processor Speed (MHz)	133Mhz	133Mhz	133Mhz
Built-in Communication Ports	One RS-485 port on power supply. Supports SNP	One RS-485 port on power supply. Supports SNP and two Ethernet ports; (one IP address) on CPU, 10/100 Mbps built-in switch, SRTP - channels (Producer and Consumer); EGD, Modbus TCP Client/Server and Web Diagnostics Support	One RS-485 port on power supply. Supports SNP and two Ethernet ports; (one IP address) on CPU, 10/100 Mbps built-in switch, SRTP - channels (Producer and Consumer); EGD, Modbus TCP Client/Server and Web Diagnostics Support
Total Number of Racks	8	8	8
Communications Option Modules	Serial-SNP, SNPX, RTU and CCM, LAN-Genius, Ethernet SRTP and Ethernet Modbus TCP Client/Server	Serial-SNP, SNPX, RTU and CCM, LAN-Genius, Ethernet SRTP and Ethernet Modbus TCP Client/Server	Serial-SNP, SNPX, RTU and CCM, LAN-Genius, Ethernet SRTP and Ethernet Modbus TCP Client/Server
Field Busses/Device Networks	Ethernet, Genius, Profibus-DP, DeviceNet, Interbus-S, CsCAN	Ethernet, Genius, Profibus-DP, DeviceNet, Interbus-S, CsCAN	Ethernet, Genius, Profibus-DP, DeviceNet, Interbus-S, CsCAN
Software Programming Support	Proficy Logic Developer - Machine Edition	Proficy Logic Developer - Machine Edition	Proficy Logic Developer -Machine Edition
Internal Power Used	1.4 Amps @ 5 VDC	1.4 Amps @ 5 VDC	1.4 Amps @ 5 VDC



CPU's

VersaMax CPUs supply a number of features usually found only in PLCs with larger footprints, including up to 128K of memory for application programs, floating point math, and real-time clock. With a modular and scalable architecture, the VersaMax CPU is ideal for standalone control applications with up to 256 local I/O or expanded systems of up to 4,096 I/O points.

	IC200CPU001	IC200CPU002	IC200CPU005	IC200CPUE05
Product Name	VersaMax PLC CPU 32K Configurable Memory, 2 Ports RS-232 and RS-485	VersaMax PLC CPU 42K Configurable Memory, 2 Ports RS-232 and RS-485	VersaMax PLC CPU 128K Con- figurable User Memory, 2 Ports RS-232 and RS-485	VersaMax PLC CPU 128K Con- figurable User Memory, 2 Ports RS-232 and RS-485, 10 MBIT Ethernet Port. Supports EGD and SRTIP.
Lifecycle Status	Active	Active	Active	Active
I/O Discrete Points	2048 in, 2048 out	2048 in, 2048 out	2048 in, 2048 out	2048 in, 2048 out
I/O Analog Words	Configurable	Configurable	Configurable	Configurable
Registers	Configurable	Configurable	Configurable	Configurable
Discrete Internal Bits	1024 points	1024 points	1024 points	1024 points
Discrete Temporary Bits	256 points	256 points	256 points	256 points
Global Discrete Bits	1280 points	1280 points	1280 points	1280 points
Program Memory	Configurable	Configurable	Configurable	Configurable
Boolean Execution Speed	1.8 ms/K (typical)	1.8 ms/K (typical)	0.8 ms/K (typical)	0.8 ms/K (typical)
Floating Points	Yes	Yes	Yes	Yes
Override	Yes	Yes	Yes	Yes
Built-in Communications	SNP Slave, RTU Master and Slave, Serial I/O	SNP Slave, RTU Master and Slave, Serial I/O	SNP Slave, RTU Master and Slave, Serial I/O	10 MBIT Ethernet Port, Slave, RTU Master and Slave, Serial I/O
Type of Memory Storage	System flash, battery-backed RAM	System flash, battery-backed RAM	System flash, battery-backed RAM	System flash, battery-backed RAM
Battery-Backed Real-time Clock	Yes	Yes	Yes	Yes
5V Backplane Current Consumption (mA)	40 with no EZ Store attached; 140 when EZ Store attached	40 with no EZ Store attached; 140 when EZ Store attached	80 with no EZ Store attached; 180 when EZ Store attached	160 with no EZ Store attached; 260 when EZ Store attached
3.3V Backplane Current Consumption (mA)	100	100	290 (Requires a power supply with 3.3 VDC expanded)	650 (Requires a power supply with 3.3 VDC expanded)
Dimensions (W x H)	2.63" (66.8 mm) x 5.04" (128 mm)	2.63" (66.8 mm) x 5.04" (128 mm)	4.20" (106.7 mm) x 5.04" (128 mm)	4.95" (126 mm) x 5.04" (128 mm)