

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

GE VERSAMAX

IC200CPUE05-EH

ETHERNET CPU MODULE

Used with the applicable VersaMax controllers configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: GE official manufacturer documentation



CPU's

VersaMax CPUs supply a number of features usually found only in PLCs with larger footprints, including up to 128K of memory for application programs, floating point math, and real-time clock. With a modular and scalable architecture, the VersaMax CPU is ideal for standalone control applications with up to 256 local I/O or expanded systems of up to 4,096 I/O points.

	IC200CPU001	IC200CPU002	IC200CPU005	IC200CPUE05
Product Name	VersaMax PLC CPU 32K Configurable Memory, 2 Ports RS-232 and RS-485	VersaMax PLC CPU 42K Configurable Memory, 2 Ports RS-232 and RS-485	VersaMax PLC CPU 128K Configurable User Memory, 2 Ports RS-232 and RS-485	VersaMax PLC CPU 128K Configurable User Memory, 2 Ports RS-232 and RS-485, 10 MBIT Ethernet Port. Supports EGD and SRTP.
Lifecycle Status	Active	Active	Active	Active
I/O Discrete Points	2048 in, 2048 out	2048 in, 2048 out	2048 in, 2048 out	2048 in, 2048 out
I/O Analog Words	Configurable	Configurable	Configurable	Configurable
Registers	Configurable	Configurable	Configurable	Configurable
Discrete Internal Bits	1024 points	1024 points	1024 points	1024 points
Discrete Temporary Bits	256 points	256 points	256 points	256 points
Global Discrete Bits	1280 points	1280 points	1280 points	1280 points
Program Memory	Configurable	Configurable	Configurable	Configurable
Boolean Execution Speed	1.8 ms/K (typical)	1.8 ms/K (typical)	0.8 ms/K (typical)	0.8 ms/K (typical)
Floating Points	Yes	Yes	Yes	Yes
Override	Yes	Yes	Yes	Yes
Built-in Communications	SNP Slave, RTU Master and Slave, Serial I/O	SNP Slave, RTU Master and Slave, Serial I/O	SNP Slave, RTU Master and Slave, Serial I/O	10 MBIT Ethernet Port, Slave, RTU Master and Slave, Serial I/O
Type of Memory Storage	System flash, battery-backed RAM	System flash, battery-backed RAM	System flash, battery-backed RAM	System flash, battery-backed RAM
Battery-Backed Real-time Clock	Yes	Yes	Yes	Yes
5V Backplane Current Consumption (mA)	40 with no EZ Store attached; 140 when EZ Store attached	40 with no EZ Store attached; 140 when EZ Store attached	80 with no EZ Store attached; 180 when EZ Store attached	160 with no EZ Store attached; 260 when EZ Store attached
3.3V Backplane Current Consumption (mA)	100	100	290 (Requires a power supply with 3.3 VDC expanded)	650 (Requires a power supply with 3.3 VDC expanded)
Dimensions (W x H)	2.63" (66.8 mm) x 5.04" (128 mm)	2.63" (66.8 mm) x 5.04" (128 mm)	4.20" (106.7 mm) x 5.04" (128 mm)	4.95" (126 mm) x 5.04" (128 mm)