

SERIES 90-30 DISCRETE I/O

Product Data Sheet

IC693MDL940H

16-point relay output module

FUNCTION	FAMILY	ORIGIN	WEIGHT
16-point relay output module	Series 90-30 discrete I/O	United States	0.80 kg

GE 90-30 Series PLC IC693MDL940H is a 16-point relay output module for the Series 90-30 discrete I/O. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Output Points	16 relay contacts
Contact Form	Normally open Form A
Output Groups	4 groups of 4
Switching Voltage	5 to 30 V DC; 5 to 250 V AC
Maximum Current	2 A per point
Minimum Load	10 mA
Response Time	15 ms maximum
Isolation	1,500 V AC field to logic
Backplane Current	490 mA at 5 V DC
Protection	External branch fusing required

- Automated storage and dispatch centers: Equipment Monitoring Systems
- Ballast pumping and deck machinery: Production Interface Systems
- Raw meal grinding and clinker handling: Material Handling Systems

Match IC693MDL940H to the installed Series 90-30 discrete I/O, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[GE official manufacturer documentation](#)

Local manufacturer PDF: IC693MDL940H.pdf