

SERIES 90-30 DISCRETE I/O

Product Data Sheet

IC693MDL940J

16-point relay output module

FUNCTION 16-point relay output module	FAMILY Series 90-30 discrete I/O	ORIGIN United States	WEIGHT 0.80 kg
---	--	--------------------------------	--------------------------

GE 90-30 Series PLC IC693MDL940J is a 16-point relay output module for the Series 90-30 discrete I/O. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Output Points	16 relay contacts
Contact Form	Normally open Form A
Output Groups	4 groups of 4
Switching Voltage	5 to 30 V DC; 5 to 250 V AC
Maximum Current	2 A per point
Minimum Load	10 mA
Response Time	15 ms maximum
Isolation	1,500 V AC field to logic
Backplane Current	490 mA at 5 V DC
Protection	External branch fusing required

- Filling and packaging production halls: Remote Station Systems
- Aeration and sludge treatment basins: Energy Management Systems
- Turbine lubrication and cooling skids: Drive Coordination Systems

Match IC693MDL940J to the installed Series 90-30 discrete I/O, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[GE official manufacturer documentation](#)

Local manufacturer PDF: IC693MDL940J.pdf