

PACSYSTEMS RX3I DISCRETE I/O

Product Data Sheet

IC694MDL754

32-point protected DC output module

FUNCTION	FAMILY	ORIGIN	WEIGHT
32-point protected DC output module	PACSystems RX3i discrete I/O	United States	0.80 kg

GE PACSystems RX3i IC694MDL754 is a 32-point protected DC output module for the PACSystems RX3i discrete I/O. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Output Points	32
Nominal Voltage	12/24 V DC
Output Range	10.2 to 30 V DC
Logic Type	Positive logic
Output Current	0.75 A per point
Output Groups	4 groups of 8
Protection	Electronic short-circuit per group
Response Time	0.5 ms maximum
Backplane Current	300 mA at 5 V DC
Terminal Block	High-density connector

- Press lines and robotic welding cells: Remote Station Systems
- Mill drives and furnace auxiliaries: Energy Management Systems
- Paper machine wet-end systems: Drive Coordination Systems

Match IC694MDL754 to the installed PACSystems RX3i discrete I/O, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[GE official manufacturer documentation](#)

Local manufacturer PDF: IC694MDL754.pdf