

PACSYSTEMS RX3I DISCRETE I/O

Product Data Sheet

IC694MDL741C

16-point negative-logic DC output module

FUNCTION	FAMILY	ORIGIN	WEIGHT
16-point negative-logic DC output modu	PACSystems RX3i discrete I/O	United States	0.80 kg

GE PACSystems RX3i IC694MDL741C is a 16-point negative-logic DC output module for the PACSystems RX3i discrete I/O. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Output Points	16
Nominal Voltage	12/24 V DC
Logic Type	Negative logic
Output Current	0.5 A per point
Output Groups	2 groups of 8
On Response	2 ms maximum
Backplane Current	110 mA at 5 V DC
Protection	External fusing required
Terminal Block	20-position removable

- Gas treatment and metering stations: Machine Control Systems
- Polymer preparation and extrusion lines: Facility Automation Systems
- Tablet compression and coating suites: Remote Station Systems

Match IC694MDL741C to the installed PACSystems RX3i discrete I/O, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[GE official manufacturer documentation](#)

Local manufacturer PDF: IC694MDL741C.pdf