

3300 XL 8MM PROXIMITY TRANSDUCER

Product Data Sheet

330106-05-30-10-02-05

3300 XL 8 mm reverse-mount probe

FUNCTION	FAMILY	ORIGIN	WEIGHT
3300 XL 8 mm reverse-mount	3300 XL 8mm Proximity Transducer	USA	0.05 kg

3300 XL 8mm Proximity Transducer 330106-05-30-10-02-05 is a 3300 XL 8 mm reverse-mount probe for the 3300 XL 8mm Proximity Transducer. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Probe mounting	Reverse mount
Case thread	M10 x 1
Armor selection	Without armor
Total probe length	1 m
Cable and connector option	Standard cable without connector protector
Agency approval option	CSA, ATEX and IECEx option; verify delivered certificate
Case material	AISI 303 or 304 stainless steel
Probe tip material	Polyphenylene sulfide (PPS)
Probe cable construction	75 ohm triaxial cable
Probe cable insulation	FEP

ADDITIONAL PRODUCT DATA

Probe operating and storage range	-52 to +177 deg C
Recommended mounting torque	7.5 N m
Connector material	Gold-plated brass or beryllium copper

OFFICIAL APPLICATIONS

- Refinery separation and storage areas: Drive Coordination Systems
- Solvent recovery and dosing rooms: Quality Inspection Systems
- Sterile filling and packaging cells: Process Control Systems

SYSTEM COMPATIBILITY

Match 330106-05-30-10-02-05 to the installed 3300 XL 8mm Proximity Transducer, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Bently Nevada official manufacturer documentation](#)

Local manufacturer PDF: 330106.pdf

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM