

3300 XL 8 MM PROXIMITY TRANSDUCER SYSTEMS

Product Data Sheet

330104-00-25-50-02-CN

eight millimeter proximity probe

FUNCTION eight millimeter proximity probe	FAMILY 3300 XL 8 mm proximity	ORIGIN United States	WEIGHT
---	---	--------------------------------	--------

3300 XL 8mm Proximity Transducer 330104-00-25-50-02-CN is a eight millimeter proximity probe for the 3300 XL 8 mm proximity transducer systems. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Probe Thread	M10 x 1
Cable Armor	Stainless steel armor
Unthreaded Length	0 mm
Overall Case Length	250 mm
Total Cable Length	5.0 m
Connector	ClickLoc without protector
Linear Range	0.25 to 2.30 mm
Scale Factor	7.87 V/mm nominal
Frequency Response	0 to 10 kHz
Target Material	AISI 4140 steel

ADDITIONAL PRODUCT DATA

Cable Impedance	75 ohm triaxial
Probe Temperature	-51 to +177 deg C
Supply Voltage	-17.5 to -26 V DC
Current Consumption	12 mA maximum

OFFICIAL APPLICATIONS

- Dryer rolls and stock preparation drives: Dryer roll bearing vibration measurement; Refiner drive shaft position tracking
- High-lift pumps and aeration blower trains: High-lift pump bearing vibration sensing; Aeration blower shaft condition measurement
- Propulsion shafts and auxiliary compressor trains: Propulsion bearing vibration measurement; Auxiliary compressor shaft position tracking

SYSTEM COMPATIBILITY

Match 330104-00-25-50-02-CN to the installed 3300 XL 8 mm proximity transducer systems, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Bently Nevada official manufacturer documentation](#)

<https://dam.bakerhughes.com/m/23d2a1de24360b13/original/3300-XL-8mm-Proximity-Transducer-System-Datasheet-141194-pdf.pdf>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM