

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

SIEMENS

6GK7343-1EX20-0XE0

INDUSTRIAL COMMUNICATION PROCESSOR

Used with the applicable Siemens Simatic Net configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: Siemens official manufacturer document: 6GK7343-1EX20-0XE0.pdf

Product type designation

CP 343-1

SIMATIC NET, CP 343-1 COMMUNICATIONS PROCESSOR FOR CONNECTION OF SIMATIC S7-300 W. IND. ETHERNET USING TCP/IP AND UDP, S7 COMM., FETCH/WRITE, SEND/RECEIVE, WITH AND W/O RFC 1006, DIAGN. EXPANS., MULTICAST LOADABLE COMMUNICATION BLOCKS, SNMP DIAGNOSIS, INITIALIZATION THROUGH LAN, 10/100 MBIT, FOR LAN RJ45 CONNECTION ONLY!

Transmission rate

Transfer rate

- at the 1st interface

10 ... 100 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

1

Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet
- for power supply

1

1

Type of electrical connection

- at the 1st interface / acc. to Industrial Ethernet
- for power supply

RJ45 port

2-pole plugable terminal block

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Supply voltage

5 V

Supply voltage / external

24 V

Supply voltage / external / at DC / Rated value

24 V

Relative symmetrical tolerance / at DC

- at 5 V
- at 24 V

5 %

5 %

Consumed current

- from backplane bus / at DC / at 5 V / typical
- from external supply voltage / at DC / at 24 V / typical

0.2 A

0.2 A

Power loss [W]

5.8 W

Ambient conditions

Ambient temperature

- for vertical installation / during operation
- for horizontally arranged busbars / during operation

0 ... 40 °C

0 ... 60 °C

during storage	-40 ... +70 °C
during transport	-40 ... +70 °C
Relative humidity	
at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-300 double width
Width	80 mm
Height	125 mm
Depth	120 mm
Net weight	0.6 kg
Mounting type	
S7-300 rail mounting	Yes

Performance data / open communication

Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	16
Amount of data	
as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum	2 Kibyte
Number of Multicast stations	16

Performance data / S7 communication

Number of possible connections / for S7 communication	
maximum	16

Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode	48
---	----

Performance data / telecontrol

Protocol / is supported	
TCP/IP	Yes

Product functions / management, configuration	
Product function / MIB support	Yes
Protocol / is supported	
• SNMP v1	Yes
• DCP	No
• LLDP	No
Configuration software	
• required	STEP 7 V5.2 or higher
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher-level designation/location designation	Yes
Product functions / Security	
Product function	
• password protection for Web applications	No
• ACL - IP-based for PLC/routing	No
• switch-off of non-required services	No
• Blocking of communication via physical ports	No
• log file for unauthorized access	No
Product functions / Time	
Product function / SICLOCK support	Yes
Product function / pass on time synchronization	Yes
Protocol / is supported	
• NTP	Yes
Further Information / Internet Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAX Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
Security information	

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

08/31/2019 