

PACSYSTEMS RX3i COMMUNICATIONS

Product Data Sheet

IC695CMM002-FK

two-port serial communications module

FUNCTION	FAMILY	ORIGIN	WEIGHT
two-port serial communications module	PACSystems RX3i communications	United States	0.80 kg

GE PACSystems RX3i IC695CMM002-FK is a two-port serial communications module for the PACSystems RX3i communications. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Serial Ports	2 isolated
Port Standards	RS-232, RS-485 and RS-422
Protocols	Modbus Master, Modbus Slave and Serial I/O
CCM Support	CCM Slave on supported firmware
Baud Rate	300 bit/s to 115.2 kbit/s
Isolation	Port-to-port and field-to-logic
Backplane Limit	6 modules per main backplane
Configuration	PAC Machine Edition
Diagnostics	Per-port status LEDs

- Paint shop and body transfer lines: Process Control Systems
- Ore conveying and screening stations: Plant Utility Systems
- Pulp washing and bleaching plants: Equipment Monitoring Systems

Match IC695CMM002-FK to the installed PACSystems RX3i communications, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[GE official manufacturer documentation](#)

<https://discreteautomation.emerson.com/>