

VERSAMAX NETWORK INTERFACES

Product Data Sheet

IC200PBI001-MH

PROFIBUS-DP network interface unit

FUNCTION	FAMILY	ORIGIN	WEIGHT
PROFIBUS-DP network interface unit	VersaMax network interfaces	United States	1.20 kg

GE VersaMax IC200PBI001-MH is a PROFIBUS-DP network interface unit for the VersaMax network interfaces. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Network Role	PROFIBUS-DP slave
Node Address	1 to 125
Data Rate	9.6 kbit/s to 12 Mbit/s auto-detected
I/O Data	375 bytes maximum
Input Data	Up to 244 input bytes
Output Data	Up to 244 output bytes
I/O Modules	64 per NIU
Diagnostics	5 user diagnostic bytes
Connector	9-pin D-sub PROFIBUS
Indicators	Power, OK, Fault, Network and Force

- Fermentation and bottling process lines: Material Handling Systems
- Filtration and disinfection stations: Safety Interlock Systems
- Generator cooling and switchyard systems: Machine Control Systems

Match IC200PBI001-MH to the installed VersaMax network interfaces, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[GE official manufacturer documentation](#)

<https://discreteautomation.emerson.com/>