

PR6423 EDDY-CURRENT SENSORS

Product Data Sheet

PR6423/003-110

8 mm eddy-current sensor

FUNCTION	FAMILY	ORIGIN	WEIGHT
8 mm eddy-current sensor	PR6423 eddy-current sensors	Germany	0.10 kg

Epro PR6423/003-110 is a 8 mm eddy-current sensor for the PR6423 eddy-current sensors. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Probe diameter	8 mm
Mounting style	Standard threaded mount
Linear measuring range	2 mm
Initial air gap	0.5 mm
Sensitivity	8 V/mm ±5%
Linearity deviation	±0.025 mm
Minimum shaft diameter	25 mm
Reference target	42CrMo4 steel
Ingress protection	IP66
Sensor temperature	-35 to +180 °C

ADDITIONAL PRODUCT DATA

Cable temperature	-35 to +150 °C
Tip material	PEEK
Housing material	Stainless steel
Cable material	PTFE

OFFICIAL APPLICATIONS

- Shaft displacement and vibration measurement: Eddy Current Measurement Systems
- Compressor rotor position monitoring: Machinery Protection Systems
- Non-contact shaft movement measurement: Condition Monitoring Systems

SYSTEM COMPATIBILITY

Match PR6423/003-110 to the installed PR6423 eddy-current sensors, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Emerson official manufacturer documentation](#)

<https://www.emerson.com/en/automation-systems/asset-performance-management/machinery-health-management/ams-pr6423>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM