

PROSAFE-RS FIO DIGITAL OUTPUT MODULES

Product Data Sheet

SDV531-S23 S4

digital output module

FUNCTION digital output module	FAMILY ProSafe-RS FIO digital output modules	ORIGIN Japan	WEIGHT 0.50 kg
-----------------------------------	---	-----------------	-------------------

Yokogawa ProSafe-RS SDV531-S23 S4 is a digital output module for the ProSafe-RS FIO digital output modules. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Output channels	8 isolated channels
Rated output voltage	24 V DC
Output voltage drop	1 V maximum
External power supply	24 V DC +20/-10%, 5 A minimum
Output current	0.6 A maximum per line
Total load current	4.8 A maximum
Minimum load current	35 mA
Load resistance	40 to 685 ohm
Output response time	30 ms maximum
Withstand voltage	2 kV AC for 1 minute

ADDITIONAL PRODUCT DATA

5 V current consumption	280 mA
24 V current consumption	140 mA
Module construction	Standard type
Operating style	S4
Module mass	0.28 kg with pressure-clamp/MIL connector

OFFICIAL APPLICATIONS

- Emergency shutdown valve stations: Safety Instrumented Systems
- Reactor interlock and shutdown panels: Process Safety Systems
- Boiler and turbine protection cabinets: Plant Protection Systems

SYSTEM COMPATIBILITY

Match SDV531-S23 S4 to the installed ProSafe-RS FIO digital output modules, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Yokogawa official manufacturer documentation](#)

Official manufacturer documentation

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM